

Contents

Vol. 67, No. 2, 2020

Energy Saving, New and Renewable Energy Sources

Conversion of Solar Radiation into Vapor: New Possibilities Offered by Nanomaterials (Review)

A. S. Dmitriev and A. V. Klimenko

Heat and Mass Transfer and Properties of Working Fluids and Materials

New Correlations for Two Phase Flow Pressure Drop in Homogeneous Flows Model

D. Maher, A. Hana, and S. Habib

Steam Boilers, Power Plant Fuels, Burner Units, and Boiler Auxiliary Equipment

A Review of Technologies for Treatment of Fuel Oil During Storage and Preparation for Burning in Boiler Units' Furnaces

N. A. Zroychikov, V. I. Kormilitsyn, V. S. Borozdin, and A. V. Pay

Application of Organic Fuel Additives to Enhance Coal Combustion Efficiency

V. E. Messerle, G. Paskalov, K. A. Umbetkaliyev, and A. B. Ustimenk

Nuclear Power Stations

Numerical Investigation into the Movement of Different Types of Molten Fuel in a Fuel Rod

E. V. Usov, I. A. Klimonov, and A. A. Butov

Revealing and Assessing the Deposit Amount on Heat-Exchanger Tubes of NPP Steam Generators According to the Operational Data of Routine Eddy Current Monitoring

A. A. Stolyarov, V. P. Lunin, A. G. Zhdanov, and E. G. Shchukis

Metals and Strength Analysis

The Influence of Low-Temperature Restorative Heat Treatment on the Structure and Mechanical Properties of Boiler Drum Metal after Long-Term Operation

S. V. Lepikhin, S. V. Gladkovskii, and O. G. Granovskii

Conversion of Solar Radiation into Vapor: New Possibilities Offered by Nanomaterials (Review)

A. S. Dmitriev^{a,*} and A. V. Klimenko^a

^a*National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia*

^{*}*e-mail: asdmitriev@mail.ru*

Received December 11, 2018; revised June 24, 2019; accepted June 26, 2019

Abstract—The current state in converting solar radiation into steam using nanotechnologies and nanomaterials is considered. The main attention is paid to the use of novel nanostructured materials, including graphene components to generate steam, in particular, to the use of the latter as floating or volumetric solar absorbers. The absorbers of the above types have been classified, their physical and technological characteristics have been considered, and preferable variants for various applications have been established. It is stressed that the question on the efficiency of surface or volumetric absorbers has to be considered as applied to specific applications. The thermophysical processes that occur during the radiation absorption and the heating of the nanofluid have been described for different absorption patterns. Models that underlie the description of the thermophotonics and nanoplasmonics processes during the solar radiation absorption by nanocomponents have been formulated. The basic processes that occur under nanoplasmonic heating of nanocomponents by solar radiation and the heat-and-mass exchange between nanocomponents and the surrounding medium have been investigated. Special attention is paid to steam generation by plasmonic nanoparticles and graphene flakes, which are currently considered the basic elements for prospective efficient solar radiation conversion systems. The properties of the materials used to absorb solar radiation and their components are described. The materials that have already shown a high solar absorption coefficient are listed. The properties of nanofluids used for volumetric absorption of solar radiation and the subsequent localized heating are described. The significant role of novel steam-generation mechanisms based on plasmonic nanoparticles and graphene flakes is stressed. Mesoscopic and nanostructured solar radiation absorbers are presented that ensure the generation of steam used not only to produce energy but also to desalinate and sterilize water. The main unsolved problems of applying nanocomponents for the solar thermal industry are considered and new tasks are set, the solution of which will allow taking important steps towards using the above systems for solar energy conversion.

Keywords: solar thermal industry, surface and volumetric adsorption, nanocomponents and nanomaterials, nanoplasmonic resonance, plasmonic nanocomposites, steam generation, graphene flakes and graphene composites

New Correlations for Two Phase Flow Pressure Drop in Homogeneous Flows Model

D. Maher^{a, c}, A. Hana^{b, *}, and S. Habib^c

^aUniversity of Sousse, Higher Institute of Agricultural Sciences of ChottMariem, Sousse, 4042 Tunisia

^bUniversity of Tunis El Manar, National Engineering School of Tunis, Le Belvedere, 1002 Tunisia

^cLaboratory of Energy and Materials (LabEM) (LR11ES34), High School of Sciences and Technology of Hammam Sousse, Sousse University, Hammam Sousse, Tunisia

*e-mail: aounethana@gmail.com

Received January 18, 2019; revised May 26, 2019; accepted June 26, 2019

Abstract—The calculation of pressure drop in pipes two-phase flow is essential in different areas. Even though several studies concerning this issue have been conducted, an accurate correlation is still required. The objective of the paper is to develop correlations for two-phase frictional pressure drop and mixture viscosity. The new correlation can be used to compute the frictional pressure drop for two phase flow in homogenous approach modeling. The original equation is generated from a similitude between the mixture viscosity for two-phase flows and the thermal conductivity of the porous structure. The new correlation is evaluated against 846 experimental data of frictional pressure drop collected from literature on circular pipes; the experimental data including different working fluids such as R1234ze (E), R32, R-600a, R717, R134a, R410A and carbon dioxide (CO₂) at different hydraulic inner diameters and mass flux. Models are assessed based on the relative percentage error and the probability density function (PDF). The predictions by the new correlation and other correlations from the literature are compared based on some experimental data. It is found that new correlation has a mean absolute relative deviation (MARD) of 30%. It is proved that these new correlations of two-phase flow pressure drop can be used to predict the experiment measurements of pressure drop, on circular pipes, minichannels and microchannels.

Keywords: pressure drop, homogenous flow, viscosity, new correlation, thermal conductivity, two phase flow, frictional

A Review of Technologies for Treatment of Fuel Oil During Storage and Preparation for Burning in Boiler Units' Furnaces

N. A. Zroychikov^{a,*}, V. I. Kormilitsyn^{b,**}, V. S. Borozdin^{c,***}, and A. V. Pay^{b,****}

^a*Krzhizhanovskii Energy Research Institute, Moscow, 119991 Russia*

^b*National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia*

^c*Scientific and Engineering Center AFT-Energo, Moscow, 111250 Russia*

^{*}*e-mail: zna@eninnet.ru*

^{**}*e-mail: KormilitsynVI@mpei.ru*

^{***}*e-mail: bvs@etstsa.ru*

^{****}*e-mail: PaiAV@mpei.ru*

Received March 21, 2019; revised June 21, 2019; accepted June 26, 2019

Abstract—The formation of nitrogen, sulfur, and carbon oxides in burning fuel oil in boiler furnaces, the elevated water content arising during unloading fuel oil from or its storage in tanks, the formation of deposits in fuel facilities' equipment during its operation, and the high cost of fuel oil are serious obstacles to the use of fuel oil as the main or backup fuel at thermal power stations (TPS). During the long-term storage of fuel oil, water partly settles and distributes in the form of lens, interlayers, or drops that are several to hundreds of micrometers in size. Water cannot be completely removed from the fuel oil by settling since the water and the fuel have nearly the same density. At present, fuel oil covers less than 2% of the fuel balance of TPSs. Considering the fact that there are regions in Russia where fuel oil is the only available fuel for boiler houses, the issues of fuel oil treatment as required for its burning or storage are urgent. Potential possibilities of the existing equipment for preparing fuel oil for burning in the form of fine water-fuel oil emulsions (WFOE) are examined, and the related performance effects are analyzed. The most promising and innovative method to produce WFOEs is the cavitation treatment of immiscible liquids. The equipment designs for cavitation treatment of viscous fluids at boiler houses and TPSs are reviewed. Preference is given to static type cavitation apparatuses featuring high capacity, reliability, and low capital and operating costs.

Keywords: fuel oil, water, fuel facilities, hydrodynamic treatment, cavitation, dispersion, emulsification, water-fuel oil emulsion, liquid fuel combustion, fuel oil storage

Application of Organic Fuel Additives to Enhance Coal Combustion Efficiency

V. E. Messerle^{a,b}, G. Paskalov^c, K. A. Umbetkaliyev^a, and A. B. Ustimenko^{d,*}

^a*Combustion Problems Institute, Almaty, 050012 Kazakhstan*

^b*Kutateladze Institute of Thermophysics, Siberian Branch, Russian Academy of Sciences, Novosibirsk, 630090 Russia*

^c*Plasma Microsystems, LLC, Torrance, CA, 90503, United States*

^d*TOO Plasmatechnics R&D, Institute of Experimental and Theoretical Physics, al-Farabi Kazakh National University, Almaty, 050010 Kazakhstan*

**e-mail: alexanderustimenko@gmail.com*

Received May 31, 2019; revised July 13, 2019; accepted August 28, 2019

Abstract—The results from numerical and experimental investigations into the influence of organic fuel additives (OFAs) on the efficiency of combusting high-ash Ekibastuz coal are presented. Technology and a special combustion chamber equipped with a plasma-assisted startup system are proposed. The thermodynamic and kinetic parameters of cocombustion of coal with OFA are numerically analyzed, as a result of which the optimum process temperatures, air-to-coal mass consumption ratios, and combustion chamber geometrical parameters have been selected. Thermodynamic analyses of the coal combustion process have shown that 7 kg of air is required to burn 1 kg of coal. A tendency toward increasing the concentrations of CO₂ and H₂O and, accordingly, toward decreasing the concentrations of NO, CO, and O₂ in the coal combustion products in using OFA has been revealed. The kinetic analysis results have shown that the coal combustion process with a consumption rate of 10 kg/h is fully completed in a combustion chamber 0.2 m in diameter and 0.9 m in height. A series of experiments on cocombustion of Ekibastuz coal with OFA was carried out. The investigation results made it possible to evaluate the effectiveness of Omstar-DX1 and Open Flame OFAs, which are prepared as mixtures of light ethers. Comparative experiments of coal combustion with and without OFAs in different concentrations (0–5 cm³ per kg of coal) have shown that the OFAs increase the flame temperature in the combustion chamber's initial part and decrease this temperature at the chamber's outlet. This means that the air–coal mixture takes less time to ignite and, accordingly, it burns out more rapidly. The introduction of OFAs results in a noticeably more efficient combustion of low-grade coal, in smaller emissions of CO and NO, and in an increased concentration of CO₂, which points to the more complete combustion of fuel.

Keywords: coal, combustion, organic fuel additives, computation, experiment

Numerical Investigation into the Movement of Different Types of Molten Fuel in a Fuel Rod

E. V. Usov^{a, *}, I. A. Klimonov^a, and A. A. Butov^a

^a*Nuclear Safety Institute, Russian Academy of Sciences, Novosibirsk Branch (NF IBRAE RAN), Novosibirsk, 630090 Russia*

**e-mail: usovev@gmail.com*

Received May 24, 2019; revised July 24, 2019; accepted August 28, 2019

Abstract—This paper presents the results from numerical investigation of the molten (metal or oxide) fuel movement on a thermal failure of a fuel rod under conditions close to a severe accident with a power surge in a fast reactor. Since experimental investigations needed to determine the regularities of an accident with core destruction cannot be carried out under actual reactor conditions due to safety reasons, getting information on the specifics of molten fuel's movement using mathematical simulation methods is urgent. The methods and approaches used in the considered problem to simulate molten fuel flow and heat transfer with the fuel-rod surface are briefly described. Although the main fuel in reactor units is an oxide fuel at present, the calculations were also performed for metallic (uranium) fuel to evaluate its effect on the development of an accident. In the calculations, account was taken for the different regularities of heat transfer of metal and oxide fuels that resulted from a considerable difference in the Prandtl numbers for melts of these materials. The processes were investigated for the first phase of severe accidents covering the period from the onset of fuel-rod melting to the melt escape from the core center. Fuel-rod melting and fuel flow were simulated for a single fuel rod.

Keywords: fuel rod, melt, simulation, fuel flow, solidification, severe accident

Revealing and Assessing the Deposit Amount on Heat-Exchanger Tubes of NPP Steam Generators According to the Operational Data of Routine Eddy Current Monitoring

A. A. Stolyarov^{a, *}, V. P. Lunin^{a, **}, A. G. Zhdanov^a, and E. G. Shchukis^a

^aNational Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

*e-mail: neron-neronov@mail.ru

**e-mail: LuninVP@mpei.ru

Received April 29, 2019; revised May 29, 2019; accepted May 29, 2019

Abstract—One of the measures aimed at preventing unscheduled shutdowns of reactor units at nuclear power plants owing to inter-circuit leaks in steam generators consists in monitoring the formation of deposits on the surfaces of heat exchangers. The azimuthal and axial extension of the electrically conductive layer in the deposits, as well as its thickness, can be used to judge the intensity of corrosion. In addition, assessing the contamination of the heat exchanger tubes from the side of the second circuit is important to prevent the accumulation of deposits on the heat exchange surfaces and to plan measures for their removal in the course of chemical washing. Monitoring conductive deposits is based on the existence of a quantitative relationship between the energy parameters of a low-frequency signal of the axial eddy-current transducer on the absolute channel and the volume of the conductive layer in the deposit. The results of studies aimed at revealing and numerically assessing the thickness (volume) of deposits on the outer surface of heat-exchanger tubes in steam generators at nuclear power plants with VVER-440 and VVER-1000 reactor units are presented. For this purpose, operational data based on standard eddy-current monitoring have been used to assess the condition of the metal in heat-exchanger tubes obtained using the PIRATE software package. At the first stage, characteristic diagnostic parameters of eddy-current signal readouts from electrically conductive deposits on heat-exchanger tubes have been determined. Criteria were then formulated according to which readouts corresponding to the sites with deposits can be automatically detected. The next stage consisted in determining the parameters of the eddy-current signal readouts that make it possible to estimate the thickness of the deposits. An algorithm has been developed for constructing a calibration curve for assessing the volume and average thickness of electrically conductive deposits on the surface of heat-exchanger tubes.

Keywords: heat-exchanger tubes, conductive deposits, multifrequency eddy current testing, energy parameter of a signal

The Influence of Low-Temperature Restorative Heat Treatment on the Structure and Mechanical Properties of Boiler Drum Metal after Long-Term Operation

S. V. Lepikhin^{a, *}, S. V. Gladkovskii^a, and O. G. Granovskii^b

^a*Institute of Engineering Science, Ural Branch, Russian Academy of Sciences, Yekaterinburg, 620049 Russia*

^b*OOO Ural Engineering and Diagnostic Center, Yekaterinburg, 620078 Russia*

* *e-mail: lepichin@mail.ru*

Received March 25, 2019; revised June 26, 2019; accepted June 26, 2019

Abstract—The drum metal properties of the BKZ-160-100FB and TP-85 boilers installed at the Irkutsk TETs-11 combined heat and power plant were investigated after these boilers had been in operation for 259 000 and 224 000 h, respectively, and after they had been subjected to low-temperature restorative heat treatment, which was carried out with steam produced by an external boiler after replacing all unions installed in the drum's water volumes. "Plugs" made of grade 22K carbon steel and of grade 16GNM low-alloy steel cut from the drum shell rings were used as research subjects. The samples were subjected to metallographic analysis, tensile tests, an impact bending test, and a hardness measurement test. The results from tensile tests carried out at room temperature and at the metal operation temperature are presented. The results from drum metal KCU notch toughness tests obtained at room temperature are given. KCV notch toughness tests were carried out for samples after their metal had been subjected to low-temperature restorative heat treatment in the temperature range from -10 to $+80^{\circ}\text{C}$. Based on the results from the KCV notch toughness tests of samples, the ductile constituent in the fractures was determined, and the drum metal ductile-to-brittle transition temperature was determined. The microstructure and mechanical properties that the drum metal had after having been in operation and having passed subsequent low-temperature restorative heat treatment were in compliance with the requirements of the relevant regulatory documents. After the boiler drum metal had been subjected to low-temperature restorative heat treatment, the studied steel samples showed a higher proof strength both at room temperature and at the operation temperature. Based on the data obtained from the investigations of boiler drum metal after it had been in operation and then subjected to low-temperature restorative heat treatment, technical diagnostics, and numerical strength analysis, it was recommended to extend the service life of the drums at their design (certificate) parameters.

Keywords: boiler drum, ferrite-pearlite steel, low-temperature restorative heat treatment, microstructure, mechanical properties, notch toughness