

Contents

Vol. 68, No. 1, 2021

Renewable Energy Sources, Hydroelectric Engineering

Modern Technologies for the Thermal Treatment of Municipal Solid Waste,
and Prospects for Their Implementation in Russia (Review)

A. N. Tugov

Nanocomposite Micropower Alternative Power Sources for Electronic Technology

A. P. Antropov, A. V. Ragutkin, M. V. Lebedeva, and N. A. Yashtulov

Designing the Main Heat-Transfer Equipment of an ORC-System
for the Internal Combustion Engines of Shipboard Installations

I. S. Antanenkova, A. P. Koroleva, M. S. Frantsuzov, A. A. Sukhikh, and V. V. Sychev

Efficiency of a Lithium Bromide Absorption Thermotransformer with Two-Stage Absorption
in the Structure of Gasified Power Plants

K. I. Stepanov and D. G. Mukhin

Application of Hydrogen–Oxygen Steam Generators for Secondary Flash Steam Superheating
at Geothermal Power Plants

G. V. Tomarov, V. I. Borzenko, and A. A. Shipkov

Steam-Turbine, Gas-Turbine, Combined-Cycle Power Plants and Their Auxiliary Equipment

The Main Directions for Improving the Efficiency of the Power Equipment of a CHP

V. E. Mikhailov, Yu. V. Smolkin, and Yu. G. Sukhorukov

Thermally Stressed State of Headers and Steam Pipelines in the Flowpath
of Combined-Cycle Power Plants during Their Heating with Condensed Steam

Yu. A. Radin and T. S. Kontorovich

Topping with a Natural Gas-Fired Combined Cycle Unit of a Coal-Fired Cogeneration
Power Plant with Cross Connections

O. V. Borush, P. A. Shchinnikov, and A. A. Frantseva

Steam Boilers, Power-Generating Fuel, Burners, and Boiler Auxiliary Equipment

A Study into the Influence of Different Factors on the Behavior of Alkaline Element
Concentrations that Cause Bed Agglomeration

G. A. Ryabov, O. M. Folomeev, O. A. Smirnova, and D. S. Litun

Modern Technologies for the Thermal Treatment of Municipal Solid Waste, and Prospects for Their Implementation in Russia (Review)

A. N. Tugov*

All-Russia Thermal Engineering Institute (OAO VTI), Moscow, 115280 Russia

*e-mail: ANTugov@vti.ru

Abstract—The data on the state-of-the-art of the thermal processing of municipal solid waste (MSW) in the United States, China, Europe, and other countries are presented. The analysis of technologies for MSW incineration in layered furnaces using fire-grates and fluidized-bed furnaces, as well as using gasification and pyrolysis, is performed. It is shown that the best technology for the energy-producing MSW utilization consists in MSW incineration in layered furnaces with the use of mechanical shearing fire-grates. It is noted that, since all the enterprises for the energy-producing MSW utilization (in fact, these are TPPs, whose main fuel is municipal solid waste) are currently equipped with multistage gas purification facilities, the problems of their environmentally safe operation are completely solved. Therefore, research is mainly aimed at improving the energy efficiency of these enterprises, including through the integration of the units for MSW incineration into the thermal circuit of a TPP operating based on fossil fuel. Examples are given of foreign operating installations for the energy-producing MSW utilization with an electrical efficiency of 27–31% as well as those operating in a heating cycle with a high energy efficiency. The state-of-the-art of MSW thermal processing and the prospects for the implementation of modern technologies for the energy-producing MSW utilization in Russia are presented. Despite the fact that there is no sufficient experience in this field in Russia (only three plants have been constructed in Moscow, whose installed electric operating capacity does not exceed 12 MW), it is planned to construct four relatively large thermal power plants in Moscow oblast with an electric operating capacity of 70 MW each, in order to incinerate 700 000 t of solid waste per year. A TPP with the energy-producing utilization of 360 000 t of MSW per year with an installed electric operating capacity of 24 MW is the most promising for Russia. Such a TPP could already be in demand in more than two dozen large Russian cities.

Keywords: municipal solid waste, energy-producing utilization, incineration, grate, TPP using MSW, energy efficiency, gasification, pyrolysis

Nanocomposite Micropower Alternative Power Sources for Electronic Technology

A. P. Antropov^a, A. V. Ragutkin^a, M. V. Lebedeva^a, and N. A. Yashtulov^{a,*}

^a*MIREA – Russian Technological University, Moscow, 119454 Russia*

*e-mail: YashtulovNA@mail.ru

Abstract—Modern process methods and approaches to production of useful electrode materials make it possible to design alternative power sources, in particular, fuel cells with high specific characteristics. Owing to their unique properties, carbon nanotubes and porous silicon are the most promising materials for developing micropower current sources. Substrates based on porous silicon have high corrosion and mechanical resistance, and they also feature a large pore surface area. Hence, the search for the best composition of matrix carriers with a large active surface and modifier metals with their minimum load is becoming an urgent process problem in power and electronic engineering. The use of metal nanoparticles in a catalyst can increase the catalytic activity in electrochemical reactions occurring in fuel cells and their corrosion resistance. Investigations into electrochemical oxidation of hydrogen and formic acid in fuel cells seem to be the most important for practice due to a wide application range of these types of fuels. This work deals with the formation of nanocomposite electrodes with nanoparticles of platinum group metals for fuel cells to be used as self-contained micropower current sources in electronic engineering. A process is described for forming effective electrode materials based on nanotubes with nanoparticles of platinum (Pt) and palladium (Pd) for low-temperature self-contained power sources. Parameters of nanocomposite electrodes in matrix-carriers are investigated by the methods of atomic-force, high-resolution transmission electron microscopy. The results from tests of formic acid–air and hydrogen–air fuel cell models are presented. The optimal loading of platinum group metals and dimensions of electrode nanocomposites giving maximum specific power and current density are found.

Keywords: alternative power engineering, fuel cells, nanocomposite electrodes, porous silicon, carbon nanotubes, watt-ampere characteristics

Designing the Main Heat-Transfer Equipment of an ORC-System for the Internal Combustion Engines of Shipboard Installations

I. S. Antanenkova^{a, *}, A. P. Koroleva^{a, b}, M. S. Frantsuzov^{b, c, **}, A. A. Sukhikh^a, and V. V. Sychev^a

^a National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

^b Baranov Central Institute of Aviation Motors, Moscow, 111116 Russia

^c Bauman Moscow State Technical University (National Research University), Moscow, 105005 Russia

*e-mail: antanenkova@mail.ru

**e-mail: mfrancuzov@yandex.ru

Abstract—The application of an electricity-generation technology involving the use, in a so-called organic Rankine cycle (ORC), of low-boiling working fluids holds promise for many fields of science and engineering in Russia. Many industrial and technological processes and operation of mechanisms and devices are often accompanied by releasing a large amount of low-grade (rejection) heat. As a rule, this heat is not usefully utilized and dissipates in the environment. Recovering the heat of exhaust gases from gas-turbine engines and diesel-generators in motor-road, railway, marine, and river transport; in gas transportation systems; in military engineering; etc. is one of the most promising application fields of this technology. In particular, an analysis of the technological parameters characterizing the operation of modern shipboard installations makes it possible to judge about the applicability of the ORC technology for improving their energy efficiency. However, the need to develop compact heat exchangers, which are designed through numerically analyzing the boiling and condensation of low-boiling working fluids (that are in themselves complex thermodynamic phenomena), is one of the most serious factors impeding the application of ORC installations in transport vehicles. The article presents a calculation procedure for preliminary designing the heat exchangers for ORC installations represented by a refrigerant vapor generator and a refrigerant condenser. The proposed procedure, which is based on the method of successive approximations, makes it possible to take into account the variability in the thermophysical properties of the used working fluids, the specific features of heat-transfer processes, changes in the geometrical parameters of the devices, the influence of process enhancement methods, etc. The article also gives results from testing the proposed procedure for the vapor generator and condenser of an ORC installation operating with R245fa fluoroorganic working fluid. The main geometrical and thermal characteristics necessary for designing the equipment of an ORC installation that recovers the heat of exhaust gases from Type 6M32 internal combustion engines used in a shipboard installation are obtained.

Keywords: organic Rankine cycle (ORC), heat-exchange equipment, low-boiling working fluids, internal combustion engine exhaust heat recovery, shipboard installations, refrigerant vapor generator, refrigerant condenser

Efficiency of a Lithium Bromide Absorption Thermotransformer with Two-Stage Absorption in the Structure of Gasified Power Plants

K. I. Stepanov^a and D. G. Mukhin^{a,*}

^aKutateladze Institute of Thermophysics, Russian Academy of Sciences, Siberian Branch, Novosibirsk, 630090 Russia

**e-mail: mukhindg@mail.ru*

Abstract—It is possible to increase the efficiency of using fossil fuels and to reduce thermal emissions into the environment and the emission of hazardous greenhouse gases by using thermotransformers (TTs) that utilize low-potential waste heat originating from man-caused sources to heat water for heating and hot water supply (HWS). As the main sources of low-grade waste heat, we have considered water circulation systems in heat power and industry as well as waste smoke fumes in boiler houses. The utilization of smoke fume heat (including latent) is the most relevant type of energy saving and of primary fuel saving, which additionally includes environmental benefits implemented by means of reducing nitrogen oxide emission. This paper proposes a scheme for the profound utilization of the heat obtained from combustion products of gas boilers using a condensation heat exchanger-utilizer and a lithium bromide absorption heat pump (LBAHP) with two-stage absorption. The analysis of the efficiency of this technology is carried out and the prospects for its implementation in gas boiler houses in Russia are considered. Studies have shown the feasibility of using LBAHP with two-stage absorption at existing large power facilities (thermal power from 116.3 MW and greater) and at small autonomous gas boiler houses (thermal power lower than 116.3 MW). The theoretical transformation ratio of LBAHP with profound utilization of smoke fumes amounts up to 1.71, whereas the saving of primary fuel in LBAHP amounts to 40% as to compared to a hot-water gas boiler. The economic effect of LBAHP significantly increases if it is used in the mode of a chilling machine for technological cooling and air conditioning in the warm season.

Keywords: utilization of low-grade heat, absorption thermotransformer, heat pump, lithium bromide, two-stage absorption, gas boiler house, smoke fumes

Application of Hydrogen–Oxygen Steam Generators for Secondary Flash Steam Superheating at Geothermal Power Plants

G. V. Tomarov^a, *, V. I. Borzenko^b, **, and A. A. Shipkov^a, *

^aOO Geoterm-M, Moscow, 111250 Russia

^bJoint Institute of High Temperatures, Russian Academy of Sciences, Moscow, 125412 Russia

**e-mail: geoatom.m@gmail.com*

***e-mail: borzenko1971@gmail.com*

Abstract—One of the promising areas of applying hydrogen technologies in power engineering is to increase the capacity utilization factor and efficiency of turbine units by means of hydrogen–oxygen steam generators for superheating the working medium under the conditions in which the surplus electricity generated at power plants during the periods of daily and seasonal reduction in electric power consumption can be used for generating hydrogen. The use of steam superheating systems on the basis of hydrogen–oxygen steam generators at geothermal power plants is especially important in view of a low energy potential of geothermal heat carrier serving as the initial heat source. The article presents the results from computational studies of the technical advisability and technical-economic efficiency of implementing systems for increasing the secondary flash steam energy potential by using a hydrogen–oxygen steam generator and a binary power unit at a direct-cycle geothermal power plant operating on steam hydrotherms. The results from computational studies into the power characteristics of a combined binary cycle geothermal power plant with secondary flash steam superheating depending on the expansion pressure variations and the hydrogen–oxygen steam generator capacity are considered. It has been determined that the use of a 12-MW hydrogen–oxygen steam generator for superheating secondary flash steam results in that the steam wetness downstream of the steam turbine last stage decreases from 14 to 7%. Calculation results have shown that the topping of a direct-cycle geothermal power plant with a system for increasing the energy potential of secondary flash steam on the basis of a hydrogen–oxygen steam generator and a binary power plant makes it possible to increase the geothermal power plant capacity by almost 25% and its efficiency by 3.0–3.5%. Based on the feasibility study results, investors can select the optimal composition and characteristics of equipment in implementing a system for increasing the energy potential of secondary flash steam using a hydrogen–oxygen steam generator and a binary power unit at a direct-cycle geothermal power plant.

Keywords: geothermal power plant, binary power unit, steam turbine, hydrogen–oxygen steam generator, steam superheating, geothermal power plant efficiency, geothermal heat carrier, combined cycle, payback period

The Main Directions for Improving the Efficiency of the Power Equipment of a CHP

V. E. Mikhailov^a, Yu. V. Smolkin^{a,*}, and Yu. G. Sukhorukov^a

^aOAO Polzunov Scientific and Development Association on Research and Design of Power Equipment (OAO NPO CKTI),
St. Petersburg, 191167 Russia

*e-mail: scheme@ckti.ru

Abstract—An important reserve for improving the thermal efficiency of an existing heat power station is the reduction of electricity generation in the condensation cycle of T- and PT-type turbines. It is advisable to develop the increase in the release of heat energy from unregulated selections of highly economical condensing turbines. For the modernization of a CHP, it is recommended to develop TR-type turbines with cogeneration backpressure. In the presence of gas fuel for new construction, it is energy efficient to install gas turbines with an electric capacity of 16 or 25 MW with hot-water heat recovery boilers or CCGTs with these turbines. Due to the significant power generation at heat-generating regimes in areas of high thermal consumption, the amount of heat-generating CCGTs is limited. These CCGTs should be developed primarily for generating electricity in the condensation cycle.

Keywords: CHP, steam turbine, gas turbine, efficiency, energy efficiency

Thermally Stressed State of Headers and Steam Pipelines in the Flowpath of Combined-Cycle Power Plants during Their Heating with Condensed Steam

Yu. A. Radin^{a,*} and T. S. Kontorovich^{a,}**

^a*PAO Mosenergo, Moscow, 119526 Russia*

**e-mail: vti-unit@yandex.ru*

***e-mail: kontorovich_ts@mail.ru*

Abstract—One of the problems arising in starting combined-cycle power units is the preheating of steam pipelines in the high- and intermediate-pressure steam path whose time has a considerable effect on the total start-up time, especially during cold start-ups. Steam condenses on the inner surface during startups of combined-cycle units in the process of increasing the pressure of high-pressure steam when the initial temperature of a heated part is below the saturation temperature or when a heated surface with a high initial temperature is exposed to the saturated steam at its current pressure for a long time. The paper considers the effect of heat transfer due to the steam condensation on the heated wall of steam pipelines (or headers) on their thermally stressed state. It has been demonstrated that the level of temperature stresses arising in the wall of the steam pipeline is insignificant with this heating since almost all the temperature difference occurs across the condensate film whose heat conductivity is much lower than that of the heated metal wall. Damages to steam pipelines, usually in the form of cracks in drainage or impulse lines near the points of their welding to the steam pipelines, are caused by the explosive nature of the boiling during pressure fluctuations in the steam pipelines and by the impact of liquid drops on the “dry” surface of the steam pipeline. The heating of the steam pipeline with increasing pressure and condensation of steam on its wall does not result in considerable thermal stresses in it during the entire stage of heating with condensed steam. Only after the saturation temperature is attained, when there is no more condensation on the wall surface of the heated steam pipeline, temperature stresses appear, whose values are determined by the temperature difference between the steam and the inner surface of the steam pipeline and convective heat-transfer coefficients which are an order of magnitude lower than those observed during heating by steam condensation.

Keywords: turbine, condensation, evaporation heat, thermal stresses, steam pipeline, header, saturation, drop condensation, film

Topping with a Natural Gas-Fired Combined Cycle Unit of a Coal-Fired Cogeneration Power Plant with Cross Connections

O. V. Borush^a, P. A. Shchinnikov^a, and A. A. Frantseva^{a, *, **}

^a*Novosibirsk State Technical University, Novosibirsk, 630073 Russia*

*e-mail: frantsevaalina@gmail.com

**e-mail: tes.nstu@gmail.com

Abstract—Thermal power plants (TPP) with cross connections and having a minimum reference fuel rate of 321 g/(kW · h) prevail in the structure of the generating capacities in Russia. In practice, this characteristic is often above 500 g/(kW · h). Application of parallel-type, dual-fuel combined-cycle units (CCUs) using coal as the main fuel, for improving the efficiency of power plants with cross connections is considered. Such CCUs have high efficiency and are suitable for modernization of operating subcritical power plants with cross connections. The power of CCUs with gas turbines manufactured in Russia or having a high degree of production localization in Russia can be as high as 200–250 MW. In all the cases, a new heat-recovery steam generator (HRSG) and a new steam turbine for a live-steam pressure of 12.8 and 8.8 MPa must be developed. The paper considers the process features of such dual-fuel cogeneration CCUs based on a 6FA gas turbine. A CCU thermal scheme is developed. Bled steam conditions under different operating conditions are determined considering the bypass of the main condensate and feedwater lines. GCU performance indices as a function of ambient air temperature are determined. In addition, an option was considered for modernizing the existing cogeneration power plant (TETs) in the town of Seversk by implementation of a dual-fuel CCU based on an 82 MW 6FA gas turbine and a T-96/122-8.8 steam turbine while maintaining the coal-fired power steam boilers in operation. It is demonstrated that the proposed modernization option makes it possible to reduce the fuel cost by approximately 240 million rubles per year while increasing the electricity delivery under cogeneration conditions by 1.7 times.

Keywords: dual-fuel CCU, binary coefficient, parallel system, fuel rate, cross connections, effectiveness

Steam Boilers, Power-Generating Fuel, Burners, and Boiler Auxiliary Equipment

G. A. Ryabov^{a,*}, O. M. Folomeev^a, O. A. Smirnova^a, and D. S. Litun^a

^a*All-Russia Thermal Engineering Institute, Moscow, 115280 Russia*

*e-mail: GARyabov@vti.ru

Abstract—In recent years, studies into the processes of bed agglomeration during the combustion of biomass have become increasingly relevant. The agglomeration processes are most largely influenced by the alkaline components of ash, which form low-melting eutectics by reacting with silicates. Therefore, it is very important to determine the critical concentration, primarily, of potassium that forms the most low-melting eutectics in the bed, at which the particles begin to sinter. The experimental studies are aimed at studying the effect of the temperature and the concentrations of alkaline elements on the process of particle agglomeration during the combustion of various types of biomass as well as biomass and coal, studying the presence of drainage, determining the critical concentration of potassium in the bed, and calculating the estimated time before the start of sintering under conditions of an increase in the concentration of potassium in the bed. The experimental techniques and characteristics of the four studied types of biomass are described. Data on the fraction of formation of agglomerated particles in the bed at different temperatures and concentrations of alkaline elements are given. Upon replacing a part of the sand by iron oxides, agglomeration is observed only at high temperatures (850°C and more). The obtained data are compared with the results of similar experiments carried out under conditions of the fluidized bed; in these experiments, the effects of the rate of fluidization, particle size, and excess air on the agglomeration processes are considered. It is noted that the limiting potassium concentration is lowest in the case of a fixed bed. It is shown that real objects should be used when studying the dependence of the behavior of the concentration of potassium in the bed on the operation time. The choice of the fraction of drainage of the bed material with the addition of a screened material or fresh sand is of practical interest. The calculation techniques and calculated data obtained with use of them on the behavior of the concentration of potassium in the bed under various conditions are presented. The fractions of bed drainage during combustion of sunflower husks and bark and wood waste are determined. In addition, it is shown that the joint combustion of husks and coal sharply reduces the probability of bed agglomeration.

Keywords: biomass, fluidized bed, agglomeration, fuel ash properties, alkali metals, low-melting compounds, research methods, potassium concentration in the bed, bed drainage, joint combustion with coal