

---

---

# Contents

---

---

Vol. 69, No. 4, 2022

---

---

## Heat and Mass Transfer and Properties of Working Fluids and Materials

Boiling in Forced Convection of Subcooled Liquid as a Method for Removing High Heat Fluxes (Review): Part 1. Characteristics, Mechanism, and Model of the Process, Heat Transfer, and Hydraulic Resistance

*N. V. Vasil'ev, Yu. A. Zeigarnik, and K. A. Khodakov*

Numerical Simulation of the Formation Process of Zones with Increased Air Content in Pipe Beams during Steam Condensation with a Small Air Foundation

*K. B. Minko, G. G. Yankov, and V. I. Artemov*

---

## Renewable Energy Sources and Hydropower

Multistage Geothermal Binary Energy Complexes: Disposal of a High Temperature Heater (180°C)

*G. V. Tomarov and A. A. Shipkov*

Carbon Dioxide Power Systems: Research Lines at Initial Design Stages and Application Prospects in Russia

*M. A. Vertkin, P. V. Egorov, S. B. Esin, S. P. Kolpakov, V. E. Mikhailov, and Yu. G. Sukhorukov*

---

## Water Treatment and Water Chemistry

Experience Gained with Chemically Cleaning the Evaporators of the Beloyarsk NPP BN-600 Reactor Plant Sodium–Water Steam Generators from Deposits

*V. F. Tyapkov, V. B. Smykov, and K. G. Legkikh*

Developing Technologies for Protective Oxidation of Equipment in the Third Circuit of a BN-800 Reactor Unit

*B. A. Gusev, A. A. Efimov, L. N. Moskvina, A. M. Aleshin, V. V. Martynov, and A. N. Maksimova*

---

## Steam-Turbine, Gas-Turbine, and Combined-Cycle Power Plants and Their Auxiliary Equipment

The Effectiveness of Film Cooling of a Flat Surface in an Accelerated Flow with Air Injection Through Fan-Shaped Holes

*E. Yu. Marchukov, A. V. Starodumov, A. V. Il'inkov, A. V. Shchukin, A. M. Ermakov, V. V. Takmoltsev, and I. A. Popov*

---

## Steam Boilers, Power-Plant Fuels, Burner Units, and Boiler Auxiliary Equipment

Dynamic Simulator for Working Processes of Steam Boilers' Furnace Devices

*E. A. Boyko, S. V. Pachkovsky, V. N. Volnev, and D. V. Surgutsky*

---

---

# Boiling in Forced Convection of Subcooled Liquid as a Method for Removing High Heat Fluxes (Review): Part 1. Characteristics, Mechanism, and Model of the Process, Heat Transfer, and Hydraulic Resistance

N. V. Vasil'ev<sup>a, b, \*</sup>, Yu. A. Zeigarnik<sup>a</sup>, and K. A. Khodakov<sup>a</sup>

<sup>a</sup> Joint Institute for High Temperatures (JIHT), Russian Academy of Sciences (RAS), Moscow, 125412 Russia

<sup>b</sup> Bauman Moscow State Technical University, Moscow, 105005 Russia

\*e-mail: [nikvikvas@mail.ru](mailto:nikvikvas@mail.ru)

**Abstract**—A review of the data on boiling of a liquid at a temperature below the saturation temperature (subcooled liquid) and on the process enabling the removal of extremely high heat fluxes is presented. The review consists of two parts. The first part describes the characteristics of the process under consideration, its phenomenological models, and the results of analysis of heat transfer and hydraulic resistance. The second part will be devoted to the analysis of studies of critical heat fluxes and heat transfer enhancement. Specific features of the process mechanism are considered, such as chaotic spatial distribution and deactivation of nucleation sites during bubble collapse and absence of a vapor phase in the flow core. The data on the characteristic sizes of bubbles and their lifetimes are given, and the evolution of the bubble shape in time is described. The Snyder–Bergles phenomenological model corresponds to the observed subcooled liquid boiling pattern best of all and offers the most plausible description of the process. It is noted that, with a decrease in the subcooling, the subcooled liquid boiling gradually loses its specific features and takes on properties typical for saturated liquid boiling. The fully developed subcooled liquid boiling is a local phenomenon whose characteristics are controlled by local process conditions (local conditions hypothesis). It is reasonable to represent the subcooled boiling heat transfer as the sum of the convective component and the boiling component  $q_{\text{boil}}$  with the heat-transfer coefficient being fit quite well by a power-law dependence on  $q_{\text{boil}}$  with an exponent of  $n = 0.65\text{--}0.70$ . The hydraulic resistance in the flow of a boiling subcooled liquid is close to the resistance in a nonboiling liquid flow with the same mass flowrate.

**Keywords:** boiling, subcooled liquid, vapor bubbles, process mechanism, heat-transfer characteristics, hydraulic resistance

# Numerical Simulation of the Formation Process of Zones with Increased Air Content in Pipe Beams during Steam Condensation with a Small Air Foundation

K. B. Minko<sup>a, b, \*</sup>, G. G. Yankov<sup>a, b</sup>, and V. I. Artemov<sup>a, b</sup>

<sup>a</sup> Kaluga State University, Kaluga, 248023 Russia

<sup>b</sup> National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

\*e-mail: minkokb@gmail.com

**Abstract**—The formation process of a zone with an increased air content during the condensation of practically pure steam in a bundle of 397 smooth horizontal pipes has been numerically studied. The layout of the simulated tube bundle completely repeated the layout of the bundle of the experimental setup of D.H. McAllister, in which air was removed through two perforated tubes located in the center of the bundle. The processes of flow and condensation of practically pure vapor (mass fraction of air  $1.22 \times 10^{-3}$ ) at a pressure of 27.67 kPa and a velocity of a horizontally directed steam flow in front of the tube bundle of 12.3 m/s. Numerical modeling was carried out using the CFD model previously published by the authors. The local characteristics of the processes of heat and mass transfer in the tube bundle have been studied. Data were obtained on the quasi-stationary position of the boundary of the zone with an increased air content (“air pocket”), as well as the velocity field of the mixture and the mass fraction of air in the condenser. A significant nonstationarity of the processes in the “air pocket” zone was revealed, which leads to a noticeable change in time of the local values of the heat flux density on the pipe walls. This effect was previously discovered experimentally, which was reflected in a few publications and regulatory documents on the calculation of the heat-exchange surface of powerful condensers. Satisfactory agreement of the obtained results of calculations of local characteristics of heat and mass transfer with D.H. McAllister’s experimental data and the identification of effects that were not detected when using models of a porous medium allow us to recommend the CFD model developed by the authors for optimizing the design of the designed condensing units.

**Keywords:** condensation, forced flow, horizontal tube bundle, mathematical modeling, heat-transfer coefficients, local characteristics

# Multistage Geothermal Binary Energy Complexes: Disposal of a High Temperature Heater (180°C)

G. V. Tomarov<sup>a, \*</sup> and A. A. Shipkov<sup>a, \*</sup>

<sup>a</sup> *OOO Geotherm-M, Moscow, 111250 Russia*

*\*e-mail: geoatom.m@gmail.com*

**Abstract**—The desire to utilize waste heat from various industrial and technological processes leads to the search for new technical solutions and the development of technologies aimed at converting the thermal energy of low-grade heat carriers into electrical energy. Today, one of the most widespread technologies for generating electricity based on the use of low-grade heat is the organic Rankine cycle, which is implemented in binary power plants. The increased interest in these technologies is explained by the fact that significant initial capital costs for the creation of binary plants and their relatively low economic performance are in most cases offset by low operating costs for fuel. The use of multistage binary power complexes can become one of the ways to increase the efficiency of waste heat utilization. Specific examples and promising possibilities for the practical use of block-cascade binary power complexes in order to utilize the heat of waste heat carriers of various industries are presented. The features of multistage schemes are studied, the operation of which is based on the principle of incremental (step-by-step) energy conversion of a high-temperature geothermal single-phase water heat carrier in binary energy complexes to increase the efficiency of using geothermal resources. Some results of computational studies of thermodynamic indicators and technical characteristics of two- and three-stage binary power complexes with a high-temperature (180°C) initial geothermal coolant are considered. The analysis of the technical characteristics of two- and three-stage binary energy complexes is carried out in comparison with the traditional single-circuit binary power unit when using various organic substances as a working fluid. It is shown that the use of a two-stage scheme makes it possible to increase the amount of heat transferred to a binary cycle by 15% in comparison with a single-stage scheme, and the use of a three-stage scheme by 18.9%. When implementing the developed methodology for numerical modeling of geothermal and binary circuits, it is possible to optimize the technological schemes of two- and three-stage binary power complexes according to the maximum installed power and minimum specific consumption of the initial geothermal fluid.

*Keywords:* geothermal heat carrier, binary energy complexes, organic working fluid, multistage scheme, specific heat carrier consumption, separat

## Carbon Dioxide Power Systems: Research Lines at Initial Design Stages and Application Prospects in Russia

M. A. Vertkin<sup>a,\*</sup>, P. V. Egorov<sup>a</sup>, S. B. Esin<sup>a</sup>, S. P. Kolpakov<sup>a</sup>, V. E. Mikhailov<sup>a</sup>, and Yu. G. Sukhorukov<sup>a</sup>

<sup>a</sup> OAO Polzunov Scientific and Development Association on the Research and Design of Power Equipment (OAO NPO CKTI),  
St. Petersburg, 191167 Russia

\*e-mail: VertkinMA@ckti.ru

**Abstract**—Carbon dioxide power systems (CO<sub>2</sub>-PS) are thermal power facilities in which carbon dioxide (CO<sub>2</sub>) is used as a working fluid. Given a fairly high initial temperature upstream of the turbine, their efficiency may be higher than that of steam turbine analogs. In all developed countries, intense studies aimed at development of CO<sub>2</sub>-PSs for various purposes are carried out, as a rule, with active participation of the state sector, including the development of state programs and addressed budgetary financial support, with the majority of R&D works carried out in the capacity of national laboratories and research institutes, with planning the works and monitoring their progress. Special attention is paid to solving the problem of decreasing the metal intensity and cost of heat-transfer equipment. It is shown—taking as an example a feasibility study of modifying the domestically developed 1200 MW sodium-cooled fast nuclear power facility by replacing the steam power plant by a CO<sub>2</sub>-PS—that such modification for large capacity power plants with moderate initial temperature levels results in degraded economic efficiency as a consequence of much higher metal intensity, larger overall dimensions, and cost of the heat-transfer equipment. Better economic efficiency in comparison with similar steam turbine plants can be achieved by increasing the initial temperature and decreasing the capacity of a single power unit. At the initial design stages, it is advisable to place the focus on developing a small capacity power part equipment of one standard size (with a standardized main compressor) intended for being used in CO<sub>2</sub>-PS at solar, nuclear, and thermal power facilities. The development of an experimental demonstration (ED) small-capacity CO<sub>2</sub>-PS intended for carrying out tests and experimentally perfecting the equipment and technology of its operation is a mandatory stage in the development of CO<sub>2</sub>-PSs for different capacities and purposes. For decreasing the cost of ED CO<sub>2</sub>-PS recuperators, it is necessary to construct a bench for testing the heat-transfer modules (HTMs) of which the CO<sub>2</sub>-PS recuperators will be assembled. A basic thermal cycle circuit of the bench facility that will accurately replicate the operation conditions of HTMs as part of the ED CO<sub>2</sub>-PS recuperators is developed. The tasks that have to be solved based on the experimental study results are described, and examples of the schematic diagrams of microchannel heat exchangers using which the HTMs can be made more compact are given. Detailed design documents for HTM equipment shall be developed in coordination with the development of technological documentation and plans for improving the technological preparation of manufacture at the industrial partner enterprise that will undertake the task of producing the ED CO<sub>2</sub>-PS heat-transfer equipment.

**Keywords:** supercritical carbon dioxide Brayton cycle, carbon dioxide power system, experimental demonstration power system, recompressing, recuperator, heat exchanger, heat-transfer module, heat-transfer module testing bench, microchannel heat exchangers

# Experience Gained with Chemically Cleaning the Evaporators of the Beloyarsk NPP BN-600 Reactor Plant Sodium–Water Steam Generators from Deposits

V. F. Tyapkov<sup>a</sup>, V. B. Smykov<sup>b</sup>, \*, and K. G. Legkikh<sup>b</sup>

<sup>a</sup> *All-Russia Research Institute for Nuclear Power Plant Operation, Moscow, 109507 Russia*

<sup>b</sup> *Leipunsky Institute of Physics and Power Engineering, Obninsk, Kaluga oblast, 249033 Russia*

*\*e-mail: smykov@ippe.ru*

**Abstract**—In the course of steam generator operation, deposits accumulate on the surfaces of their structural materials, whatever the steam generator type. These deposits consist of corrosion products, various nonvolatile salts and bases, organic impurities, and other compounds. Iron oxides impregnated with water-soluble salt impurities form the base of the chemical composition of these deposits. This medium is corrosive in nature and can eventually give rise to local corrosion of structural material. This process results in that the coolant flowrates decrease, heat transfer becomes less intense, local corrosion occurs under the deposits, and, as a consequence, a steam generator leak occurs. Such problems are solved in the main by cleaning the steam generator with a cleaning solution containing chemically active components. In view of great experience gained with implementing similar measures in various industry sectors, it is especially worth noting the technology of carrying out operational chemical cleanings (OCC) of sodium–water type steam generators, which have a number of specific features both during their normal operation and in carrying out OCCs aimed at preventing loss of their circuit-to-circuit tightness. In view of this, the OCC conducting technology needs the process to be continuously monitored. For the time that the BN-600 reactor plant (RP) had been in operation, the steam generator evaporators were regularly subjected to operational chemical cleanings. Chemical cleanings are carried out with sodium circulating in the secondary circuit for continuously monitoring the circuit-to-circuit tightness of the evaporators being cleaned. The applied chemical cleaning technology and the composition of chemical solutions have shown their chemical effectiveness and safety. The experience gained with operation of the BN-600 reactor plant steam generator is generalized. Recommendations on optimizing the monitoring of the OCC main parameters, on-line monitoring of the process, changing the composition of cleaning solution components, and solution reprocessing methods are formulated.

*Keywords:* steam generator, operational chemical cleaning, BN-600 reactor plant, circulation loop, iron corrosion products, corrosion rate, cleaning solution, passivation, loss of circuit-to-circuit tightness

## Developing Technologies for Protective Oxidation of Equipment in the Third Circuit of a BN-800 Reactor Unit

B. A. Gusev<sup>a,\*</sup>, A. A. Efimov<sup>a</sup>, L. N. Moskvina<sup>a</sup>, A. M. Aleshin<sup>a</sup>, V. V. Martynov<sup>a</sup>, and A. N. Maksimova<sup>a</sup>

<sup>a</sup> *Alexandrov Scientific Research Technological Institute, Sosnovy Bor, Leningrad oblast, 188540 Russia*

*\*e-mail: gusev@niti.ru*

**Abstract**—The results of the development of alternative technologies for directional protective oxidation of working surfaces of equipment made of pearlitic steels for the evaporating and superheating modules of the N-272 vertical steam generator (SG) of the BN-800 reactor unit (RU), operated under the conditions of an oxygen-ammonia water-chemical regime, are presented. The formation of protective oxide films of magnetite with desired properties occurs during the thermolysis of aqueous solutions of complexonates and iron complexes with various ligands in contact with the surface of pearlite-class steels. Two-stage technologies of directional oxidation are based on the use of solutions of ammonium acetate or Trilon B. The chemical forms of iron compounds in working solutions for the formation of high-quality protective films have been established. At the first stage, associates of “oxidizing” Fe(III) complexes with elemental iron atoms in active centers of metal dissolution are formed. At the second stage, the thermal decomposition of the associates occurs with the formation of nuclei of magnetite crystals, which retain the chemical bonds that have arisen in the associates between the metal atoms in the crystal lattice of steel and in the dissolved Fe(III) complex. The temperature range of thermal decomposition of associates of primary Fe(III) complexes in contact with iron atoms on the steel surface for the implementation of the formation of oxide films has been established. The compositions of the solutions and the parameters of the protective oxidation process by acetate and complex technologies have been substantiated, and the protective properties of the formed oxide films have been established. A combined technology of complex oxidation with the transformation of the washing solution into a solution of directional oxidation has been developed, which makes it possible to drastically reduce the volume of generated liquid waste. Recommendations are given for choosing the optimal variant of the oxidation technology, taking into account the thermal characteristics of the equipment.

*Keywords:* vertical steam generator, pearlite steels, oxidizing water-chemical regime, oxide films, phase composition, two-stage oxidation technology, composition of solutions, corrosion rate

# The Effectiveness of Film Cooling of a Flat Surface in an Accelerated Flow with Air Injection Through Fan-Shaped Holes

E. Yu. Marchukov<sup>a</sup>, A. V. Starodumov<sup>a</sup>, A. V. Il'inkov<sup>b</sup>, A. V. Shchukin<sup>b, \*</sup>,  
A. M. Ermakov<sup>b</sup>, V. V. Takmoltsev<sup>b, \*\*</sup>, and I. A. Popov<sup>b</sup>

<sup>a</sup> Lyulka Experimental Design Bureau, Moscow, 129301 Russia

<sup>b</sup> Tupolev Kazan National Research Technical University, Kazan, 420111 Russia

\*e-mail: a.v.shchukin@rambler.ru

\*\*e-mail: vvt379@rambler.ru

**Abstract**—In an accelerating flow, the effectiveness of film cooling by injecting air through cylindrical holes at the initial mixing section increases in comparison with a zero-pressure-gradient flow. This is caused by a decrease in the separation of the air jets injected through the holes from the cooled wall. With distance from the injection section, the cooling effectiveness of coolant injection through cylindrical holes decreases in comparison with a zero-pressure-gradient flow. The cause is the enhancement of rotation of large-scale paired vortex structures called kidney vortices. Comparative experimental studies into the effectiveness of film cooling with air injection through fan-shaped or cylindrical holes in an accelerating flow have demonstrated that different mechanisms of interaction between the secondary and main flows exist in the entrance and main mixing sections in both cases. In the performed experiments, single-row belts of both types of holes had five holes in a row. A dimensionless complex of film-cooling effectiveness in an accelerating flow was used for a comparative analysis of the relative film-cooling effectiveness on a flat surface with injection through fan-shaped and cylindrical holes. At angles of secondary air injection into the main flow of  $\alpha = 30^\circ$ ,  $45^\circ$ , and  $75^\circ$ , the acceleration of the main flow has a different effect on the relative value of the film-cooling effectiveness for a flat surface,  $\bar{\eta}$ , with injection through fan-shaped or cylindrical holes at the best ( $m = 0.5$ ) or high ( $m = 2.5$ ) blowing ratio. Thus, for  $m = 0.5$ , the value of  $\bar{\eta}$  in the entrance mixing section at  $\alpha = 30^\circ$  is 0.3, but the cooling effectiveness is hardly affected by it when  $\alpha = 45^\circ$  and  $75^\circ$ . For  $m = 2.5$ , the values of  $\bar{\eta}$  at  $\alpha = 30^\circ$ ,  $45^\circ$ , and  $75^\circ$  are, respectively, 1.35, 1.15, and 2.15. In the main mixing section, for  $m = 0.5$ , the value of  $\bar{\eta}$  increases (1.0, 1.15, and 1.6) when the injection angle increases; for  $m = 2.5$ , it decreases in comparison to the zero-pressure-gradient value from 1.6 at  $\alpha = 30^\circ$  to 0.72–0.82 at  $\alpha = 45^\circ$  and  $75^\circ$ .

**Keywords:** physical experiment, surface film cooling, hole belt, cylindrical and fan-shaped holes, blowing ration, injection angle, flow acceleration



# Dynamic Simulator for Working Processes of Steam Boilers' Furnace Devices

E. A. Boyko<sup>a, \*</sup>, S. V. Pachkovsky<sup>a</sup>, V. N. Volnev<sup>a</sup>, and D. V. Surgutsky<sup>a</sup>

<sup>a</sup> Siberian Federal University, Krasnoyarsk, 660041 Russia

\*e-mail: Eboiko@sfu-kras.ru

**Abstract**—An approach to simulating and controlling a pulverized coal furnace with taking into account the fuel combustion and complex heat transfer processes is considered. A distinguishing feature of the methodical approach presented in the article is that individual calculated zones are separated in the furnace chamber according to their functional features and physicochemical homogeneity, and also that it is possible to take into account the reaction characteristics of individual thermochemical conversion processes and, hence, the quality of fuel combusted. The procedure of dividing the furnace chamber into zones is based on using the theoretical model of a flow-type reactor with ideal mixing without heat removal through the wall with taking into account kinetic resistance to combustion. The model assumes zero gradients of both fuel and oxidizer concentrations, due to which there is no diffusion resistance to combustion. The mathematical description of the modeled equipment local areas, which are dynamically divided in the vertical and horizontal directions into sequential chains of volume and surface zones, is given in the class of ordinary differential equations with retaining all essential features of the process, such as multiplicity of stationary states and critical levels of furnace volume calorific intensity corresponding to flame failures. The mathematical model and comparative computation results for a few furnaces in combusting different kinds of coal are given. Based on the proposed analysis procedure, a dynamic computer simulator for perfecting the working processes running in steam boiler furnace devices (a training simulator) has been developed. By using this simulator, the thermal power plant (TPP) personnel can be trained to perform operative control of furnace process in the boiler unit with the possibility of changing the state of auxiliary equipment and operating parameters of the unit as a whole and of its individual functional groups.

*Keywords:* furnace, combustion modes, optimization of furnace processes, computer simulator