

# Contents

---

---

Vol. 69, No. 6, 2022

---

---

## General Subjects

Digitalization and Digital Transformation of the Thermal-Power Industry as a Factor of Improving the Thermal Infrastructure Efficiency (Review)

*E. Yu. Golovina, E. V. Samarkina, N. E. Buinov, and M. V. Evloeva*

3

---

## Steam-Turbine, Gas-Turbine, and Combined-Cycle Power Plants and Their Auxiliary Equipment

Cofiring of Coal and Fossil Fuels is a Way to Decarbonization of Heat and Electricity Generation (Review)

*G. A. Ryabov*

17

---

## Renewable Energy Sources and Hydropower

Experimental and Numerical Studies into the Cavitation Impact of the Hydrofoil Surface with Different Treatments

*M. Sedlář, M. Komárek, J. Šoukal, A. V. Volkov, A. V. Ryzhenkov, A. A. Druzhinin, S. V. Grigoriev, G. V. Kachalin, and O. V. Kalakutskaya*

33

---

## Heat and Mass Transfer, Properties of Working Bodies and Materials

Creation of Hydrophobic Functional Surfaces of Structural Materials on the Basis of Laser Ablation (Review)

*A. V. Ragutkin, M. R. Dasaev, O. V. Kalakutskaya, O. S. Zilova, and E. S. Trushin*

46

---

## Nuclear Power Plants

High-Speed Passive Shut-Off Device for Shut-Off of Feed-Water Flow in a Brest-Type Reactor Facility in Accidents with Solidification of the Lead Coolant

*A. S. Chistov, O. G. Savikhin, and V. F. Ovchinnikov*

70

Results of Verification and Validation of the Oxid Module of the EUCLID/V2 Integral Code in Part of Physicochemical Models of Processes in a Lead Coolant

*V. I. Chukhno, D. A. Nazarov, A. A. Sorokin, T. V. Sycheva, E. V. Usov, and N. A. Mosunov*

78

---

## District Heating Cogeneration and Heat Networks

Analysis on the Technical Situation and Applied Difficulties of District Heating Load Forecasting

*Bingwen Zhao, Yu Jin, Wan Li, and Hanyu Zheng*

86

---

---

# Digitalization and Digital Transformation of the Thermal-Power Industry as a Factor of Improving the Thermal Infrastructure Efficiency (Review)

E. Yu. Golovina<sup>a, \*</sup>, E. V. Samarkina<sup>a</sup>, N. E. Buinov<sup>a</sup>, and M. V. Evloeva<sup>a</sup>

<sup>a</sup> Irkutsk National Research Technical University, Irkutsk, 664074 Russia

\*e-mail: elena\_uspeh@mail.ru

**Abstract**—Innovative development is a key factor for achieving more efficient performance of fuel-and-energy complex (FEC) enterprises, and also more reliable and economically efficient supply of energy to consumers on the basis of state-of-the-art technologies with transforming them into an intelligent core of the thermal-power industry’s technological infrastructure. Information technologies continue to actively penetrate into all key fields of human activity and economy sectors; they are a condition for competitiveness and economic development of the country and for further improvement in people’s quality of life. The current stage of this process has been defined as “digital transformation.” It is characterized by an entirely new feature: digital technologies transfer from the category of auxiliary tools to the category of capital goods. This process also has touched the fuel-and-energy complex. Transition to a digitalized operation mode is a response to external technological challenges and future structural changes in the power system. The article studies the goals pursued by digital transformation of thermal-power industry companies. The influence of the thermal-power industry’s digitalization and digital transformation on energy saving and improvement of energy efficiency and energy infrastructure performance quality is considered. Practical experience of implementing digital technology introduction projects aimed at energy-efficient upgrading of heat-supply systems is presented. Fundamental works of foreign and domestic authors in the field of digital economy are considered. Based on the study results, a refined system of concepts is presented; the authors’ own approach to digital transformation components is proposed, and categories lying at the heart of Industry 4.0 are identified, which include a certain set of digital technologies, including prospective ones, from the viewpoint of applying them in the thermal-power industry.

*Keywords:* Industry 4.0, automation, thermal-power industry digital transformation, energy efficiency, Smart Grid, intelligent data processing

# Cofiring of Coal and Fossil Fuels is a Way to Decarbonization of Heat and Electricity Generation (Review)

G. A. Ryabov\*, \*\*

*All-Russia Thermal Engineering Institute (OAO VTI), Moscow, 115280 Russia*

*\*e-mail: GARyabov@vti.ru*

*\*\*e-mail: georgy.ryabov@gmail.com*

**Abstract**—Cofiring of coal and biomass has been demonstrated to be a promising solution to the problem of partial decarbonization of electricity and heat generation. This technology meets the aims of sustainable development of the world community and complies with the UN documents on environment protection and control of greenhouse gas emission. The properties of biomass, which largely determine the selection of one or another solution for its cofiring with fossil fuels, are discussed. The biomass pretreatment, which makes the biomass properties closer to the coal properties, is important. The pretreatment techniques, including leaching, pelletization, torrefaction, and steam explosion, are examined. Data are presented on the process solutions in the form of direct or indirect combustion (gasification followed by combustion). The greatest share of biomass in cofiring can be attained with fluidized bed (FB) and circulating fluidized bed (CFB) technologies. Circulating fluidized bed boiler, their performance indicators, and the problems arising in their operation (such as slagging, bed agglomeration, fouling and corrosion of heating surfaces) are presented. It has been found that, compared to the conventional technology, the oxygen supported cofiring of coal and biomass in a CFB boiler can considerably reduce the recorded CO<sub>2</sub> emission. The prospects are discussed concerning the application cofiring technologies in Russia, where huge reserves of unused wood and plant waste are available. It is demonstrated that requirements to reduce the carbon footprint in products may be an additional drive for the implementation cofiring technologies. However, this requires additional research and engineering activities, including studies of biomass pretreatment, safety of cofiring facilities, formation and control of harmful emission, especially during combustion in an oxygen environment with CO<sub>2</sub> recirculation, the effect of biomass components (such as alkaline elements and chlorides) on the formation of deposits on heating surfaces, their corrosion, and bed agglomeration.

*Keywords:* biomass, coal, cofiring, decarbonization, fluidized bed, harmful emissions, boiler operation, mathematical modelling, oxygen combustions

# Experimental and Numerical Studies into the Cavitation Impact of the Hydrofoil Surface with Different Treatments

M. Sedlář<sup>a,\*</sup>, M. Komárek<sup>a</sup>, J. Šoukal<sup>a</sup>, A. V. Volkov<sup>b,\*\*</sup>, A. V. Ryzhenkov<sup>b</sup>, A. A. Druzhinin<sup>b</sup>, S. V. Grigoriev<sup>b</sup>, G. V. Kachalin<sup>b</sup>, and O. V. Kalakutskaya<sup>b</sup>

<sup>a</sup> Hydraulic Research Center Sigma, Lutín, 78349 Czech Republic

<sup>b</sup> National Research University Moscow Power Engineering Institute (NRU MPEI), Moscow, 111250 Russia

\*e-mail: m.sedlar@sigma.cz

\*\*e-mail: volkovav@mpei.ru

**Abstract**—The experimental and numerical investigation of unsteady cavitating flow around a NACA2412 hydrofoil with chemically treated surfaces is described. The study was focused on the influence of the surface wettability on the intensity of cavitation processes. Two steel hydrofoils whose surface is treated using different methods are compared with a hydrofoil having a nontreated surface. The first of the treated hydrofoils has a 50–70- $\mu\text{m}$  thick wear-resistant hydrophobic coating of tungsten carbide applied by ion-plasma deposition in a vacuum chamber. The second hydrofoil has a coating of a surfactant, octodecylamine, applied by deposition while keeping the hydrofoil in an aqueous solution. The hydrofoil with the span/chord ratio of 1.25 was tested in the cavitation tunnel. The incidence angle of the hydrofoil to the incoming flow was  $8^\circ$ . Numerical results were obtained using the ANSYS CFX software package with the Zwart cavitation model and the SAS-SST turbulence model. The monitored pressure fluctuations and the level of noise generated by cavitation-induced unsteady processes are estimated. It is demonstrated that additional surface treatment can help prevent unwanted phenomena in the flow path caused by cavitation. This technique does not require expensive modernization of the flow path in hydraulic machines. Numerical simulations and experiments carried out by the authors suggest that surface treatment can considerably affect the cavitation processes, and the results of studies demonstrate the need for further in-depth investigation of cavitation processes in hydraulic machines, including with the use of modern application software tools.

*Keywords:* hydrofoil, cavitation tunnel, CFD, partial cavitation oscillation, surface wettability, coating

# Creation of Hydrophobic Functional Surfaces of Structural Materials on the Basis of Laser Ablation (Review)

A. V. Ragutkin<sup>a,\*</sup>, M. R. Dasaev<sup>a</sup>, O. V. Kalakutskaya<sup>a</sup>, O. S. Zilova<sup>a</sup>, and E. S. Trushin<sup>a</sup>

<sup>a</sup> MIREA – Russian Technological University, Moscow, 119454 Russia

\*e-mail: [dasaev@mirea.ru](mailto:dasaev@mirea.ru)

**Abstract**—Over the past decade, interest has increased in controlling the wettability of metal surfaces with various liquids. In particular, the use of hydrophobic functional surfaces improves the efficiency and reliability of thermal power plants and systems operating in various areas of life. One of the most promising ways to achieve a hydrophobic state of structural materials is surface modification using laser equipment: laser ablation. As a result of exposure to laser radiation, melting, evaporation and recrystallization of the surface layer of the metal occur. By varying the parameters of exposure to laser radiation, it is possible to form a relief with specified geometric characteristics on a metal surface. The creation of hydrophobic metal surfaces using laser equipment includes the following steps: choosing the type of laser source, determining the radiation parameters and the trajectory of the laser beam over the surface, preparing the initial surface, forming the relief, and reducing the surface energy after laser ablation. This paper presents an overview of the results of research on the creation of hydrophobic metal surfaces based on the formation of a structured relief. In most studies, a relief was formed on the surface of metal samples in the form of equidistant lines, a grid, or had no pronounced structure (irregular structure). It has been established that the hydrophobic state of a metal surface with the highest contact angles (more than 150°) is achieved by laser texturing of the relief in the form of equidistant lines or a grid with a step not exceeding 100 μm. The maximum contact angle (approximately 179°) was obtained by forming a relief in the form of a grid with mutually perpendicular lines equidistant at 15 and 20 μm.

**Keywords:** laser texturing, laser ablation, metal surfaces, relief, wettability, hydrophobicity, surface roughness, surface energy reduction

# High-Speed Passive Shut-Off Device for Shut-Off of Feed-Water Flow in a Brest-Type Reactor Facility in Accidents with Solidification of the Lead Coolant

A. S. Chistov<sup>a, \*</sup>, O. G. Savikhin<sup>b</sup>, and V. F. Ovchinnikov<sup>a</sup>

<sup>a</sup> *Research Institute of Mechanics, UNN, Nizhny Novgorod, 603022 Russia*

<sup>b</sup> *Institute of Information Technologies, Mathematics and Mechanics, UNN, Nizhny Novgorod, 603022 Russia*

*\*e-mail: chistov@mech.unn.ru*

**Abstract**—A technical description and calculation justification for the use of a fast-acting passive device for shutting off the feed-water flow in the second circuit of a lead-cooled reactor facility of the BREST-OD-300 type are presented. The main purpose of the device is an emergency termination of heat removal in steam generators in case of accidents with the formation of a solid phase in the lead coolant. The device is a glandless through valve, the locking element of which moves from the operating position to the emergency position under the action of gravity when the feed-water pressure drops below the set value corresponding to the beginning of the solidification of the lead coolant. It is installed on the section of the feed-water pipeline at the inlet to the steam generators. The method for calculating the thermal-hydraulic and dynamic characteristics of the device is presented. Calculation estimates of its efficiency are carried out using the example of accidents caused by a rupture of the main steam header as well as a failure of the regenerative feedwater heating system in a BREST-OD-300 reactor plant. It is shown that the use of a passive shut-off device makes it possible to completely eliminate the possibility of the formation of a solid phase of lead in steam generators during these accidents and increase the level of natural self-protection of the reactor. The results of the study can be used in the development of projects for reactors with heavy liquid metal coolants.

*Keywords:* locking element, steam generator, passive shut-off valve, feed water, reactor plant, I and II circuits, lead coolant, solid phase

# Results of Verification and Validation of the Oxid Module of the EUCLID/V2 Integral Code in Part of Physicochemical Models of Processes in a Lead Coolant

V. I. Chukhno<sup>a</sup>, D. A. Nazarov<sup>a</sup>, A. A. Sorokin<sup>a</sup>, T. V. Sycheva<sup>a</sup>, E. V. Usov<sup>a,\*</sup>, and N. A. Mosunova<sup>a</sup>

<sup>a</sup> *Institute for Problems of Safe Development of Nuclear Power Engineering, Russian Academy of Sciences, Moscow, 115191 Russia*

*\*e-mail: usovev@gmail.com*

**Abstract**—Models of physicochemical processes in a lead coolant, which can be used as part of the CFD code to justify the coolant technology, and as part of an integral code to describe the state of the reactor plant at the time of the start of the simulated dynamic regime are presented. The described models are integrated into the OXID module of the EUCLID/V2 integral code developed at the Institute for Problems of Safe Development of Nuclear Power Engineering, Russian Academy of Sciences. The OXID module makes it possible to calculate, on the basis of a two-layer model, the growth of an oxide film in a lead coolant on the surface of a metal that is in contact with liquid lead, the crystallization of dissolved oxides on the channel walls, the formation of lead oxide particles (nucleation) in a coolant flow, the coagulation of solid oxide particles in a lead coolant, the deposition of oxide particles on the channel walls, the crystallization of dissolved oxides on particles and dissolution of oxide particles in the lead coolant, and the transfer of formed impurities in the coolant. A system of relationships and equations is given that allows modeling of these processes as part of a software module. By integrating this module into the EUCLID/V2 code, it is possible to carry out connected calculations of physical and chemical processes in a lead coolant, which are typical for various operating conditions of a BREST-OD-300 reactor plant. To demonstrate the performance of the implemented models, the results of verification based on analytical tests and validation based on experimental data on the growth of an oxide film on the surface of stainless steel at different concentrations of oxygen in lead, obtained at the AO SRC RF-IPPE on the CM-2 circulation stand, are presented. The validation made it possible to estimate the errors in the calculation of individual parameters important for safety.

*Keywords:* reactor plant, lead coolant, oxide film, OXID module, integral code EUCLID/V2

# Analysis on the Technical Situation and Applied Difficulties of District Heating Load Forecasting

Bingwen Zhao<sup>a</sup>, Yu Jin<sup>a, \*</sup>, Wan Li<sup>a</sup>, and Hanyu Zheng<sup>a</sup>

<sup>a</sup> Zhejiang Sci-Tech University, Xiasha Higher Education Zone, Hangzhou, Zhejiang, 310018 P.R. China

\*e-mail: 1042809345@qq.com

**Abstract**—As an effective means of energy use, district heating is widely used all over the world. The 4th generation of district heating further puts forward the concept of smart thermal grids and emphasizes the application of heating load prediction technology. This paper mainly reviews the three core elements of data preprocessing, modeling method and input eigenvalue, which affects the accuracy of heating load prediction. At the same time, based on the actual engineering investigation, the difficulties in the application of heating load forecasting in actual engineering are analyzed. On this basis, in order to promote the adoption rate of the 4th generation district heating, the application of heating load prediction in practical engineering is optimized from the following two aspects: enrich and perfect the heating load forecasting database to provide sufficient data support for the heating load forecasting; A partitioning scheme for data set construction of heating load prediction model is proposed in order to improve the accuracy of the prediction model. In order to prove the applicability of the proposed methods, the methods are applied to a district heating system in Kaifeng, and the results show that the prediction effect is obviously improved.

*Keywords:* district heating, heat load forecast, smart thermal grids, database, heating demand, pipe network, heat station