
Contents

Vol. 70, No. 3, 2023

General Subjects

Struggle for Climate Saving: The Euphoria of Plans against Cold Reality

V. V. Klimenko, A. V. Klimenko, A. G. Tereshin, and O. V. Mikushina

Heat and Mass Transfer and Properties of Working Fluids and Materials

Simulation of Condensation of Stagnant or Moving Saturated Vapor on a Horizontal Tube
Using the Volume-of-Fluid (VOF) Method

K. B. Minko, V. I. Artemov, and A. A. Klement'ev

Gradient Thermometry in the Study of Heat Transfer during Boiling in a Large Volume
of Uncooled Water and Liquid with the Addition of Al₂O₃ Microparticles

A. V. Pavlov, P. G. Bobylev, and S. Z. Sapozhnikov

Mixing of Different Temperature Flows of Liquid Sodium in the Pipeline Behind the Tee

*I. V. Kolesnichenko, R. I. Khalilov, A. V. Shestakov, A. N. Krylov, V. V. Pakholkov,
A. M. Pavlinov, A. D. Mamykin, A. Yu. Vasiliev, S. A. Rogozhkin, and P. G. Frick*

Investigation into the Emissivity of a Thin Tungsten Wire with Oxidized Surface
in the Unsteady Heat Conduction Regime

M. G. Zeodinov, A. A. Pronkin, and D. A. Krynitskaya

Steam Turbine, Gas Turbine, and Combined-Cycle Power Plants and Their Auxiliary Equipment

Study of Turbine Cascades at Negative Incidence Angles

B. I. Mamaev and G. V. Ermolaev

Nuclear Power Plants

Main Results of the Trial Test of a Closed Circuit with Natural Circulation
of a Light-Water Coolant Under Supercritical Pressure

A. A. Sedov, P. S. Polyakov, S. B. Pustovalov, V. V. Parshin, and S. S. Simonova

District Heating Cogeneration and Heat Networks

Climate Change and Its Influence on the Energy Engineering Complex
(Taking St. Petersburg as an Example)

D. A. Mil'kov, Yu. V. Yuferev, A. I. Tyutyunnikov, and A. S. Gorshkov

Struggle for Climate Saving: The Euphoria of Plans against Cold Reality

V. V. Klimenko^{a, b, c, *}, A. V. Klimenko^c, A. G. Tereshin^{a, b}, and O. V. Mikushina^{a, b}

^a National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

^b Energy Research Institute, Russian Academy of Sciences, Moscow, 117186 Russia

^c National University of Science and Technology MISIS, Moscow, 119049 Russia

*e-mail: nilgpe@mpei.ru

Abstract—Possible outcomes from the decisions adopted at the COP26, the latest Conference of the Parties to the UN Framework Convention on Climate Change (UNFCCC), for the world energy and upcoming climate changes are studied. The article suggests a group of scenarios for man-induced impacts on the global climatic system, which includes implementation of the COP26 decisions in the field of world economy decarbonization, reduction of methane emissions, and reforestation as well as alternative world energy development scenarios based on a low globe population growth level from the viewpoint of preventing dangerous global climate changes. By using the global carbon cycle and climate models developed at the National Research University Moscow Power Engineering Institute (NRU MPEI), changes in the chemical composition and thermal radiation balance of Earth's atmosphere, as well as the global average air temperature, are evaluated for each scenario. It is shown that global warming by 1.5°C can only be kept if the entire range of measures suggested at COP26 on reducing the man-induced impact on Earth's climatic system is implemented in the full scope while keeping the energy consumption and world population growth rates at the contemporary levels; however, there are serious doubts as to whether the proposed world economy decarbonization program can really be implemented. At the same time, the natural demographic processes are able to curb the growth of carbon dioxide concentration in the atmosphere and decrease it even before the end of this century. In that case, the increase in the global average temperature by 1.8°C in comparison with that in the preindustrial period (1850–1900) may be quite safe and will not require large-scale reformation of the world energy sector.

Keywords: energy, climate, atmosphere, demography, forest management, methane and carbon dioxide emissions, models, scenarios, global average temperature

Simulation of Condensation of Stagnant or Moving Saturated Vapor on a Horizontal Tube Using the Volume-of-Fluid (VOF) Method

K. B. Minko^{a, *}, V. I. Artemov^a, and A. A. Klement'ev^a

^a National Research University Moscow Power Engineering Institute (NRU MPEI), Moscow, 111250 Russia

*e-mail: minkokb@gmail.com

Abstract—The processes of film condensation of stagnant and moving vapor on a single tube and various tube bundles were examined in many studies. Nevertheless, the local characteristics of heat transfer and the details of the interaction of the flowing down condensate with a moving vapor flow, which can have a significant effect on the characteristics of the condensation process in tube bundles, are not well understood. The paper presents the results of simulation of the condensation of practically stagnant and of moving saturated vapor on a horizontal cylinder. The mathematical model of a two-phase flow is based on the Volume of Fluid (VOF), which is implemented in the open ANES research code. The main advantage of the proposed simulation method is that it can capture the interface without any assumptions. The modified Lee model was used to model interfacial mass transfer. An algorithm is proposed for the automatic selection of a constant in this model on the basis of the specified properties of the coolant and parameters of the computational grid. The model was validated against the classical Nusselt solutions for a vertical plate and a horizontal cylinder, known calculating correlations, and predictions obtained using a simplified condensation model proposed by the authors of this paper in previous studies. Information is presented on the drip-off diameters of droplets, the dynamics of heating of subcooled condensate droplets after their drip-off from the tube surface, and the effect of external tube spraying on the condensation rate. The obtained data are compared with the available experimental results.

Keywords: condensation, mass transfer, horizontal tube, interface, numerical simulation, VOF method, modified Lee model, downward vapor flow, condensate spraying, control volume

Gradient Thermometry in the Study of Heat Transfer during Boiling in a Large Volume of Uncooled Water and Liquid with the Addition of Al_2O_3 Microparticles

A. V. Pavlov^{a,*}, P. G. Bobylev^a, and S. Z. Sapozhnikov^a

^a Peter the Great St. Petersburg Polytechnic University, St. Petersburg, 195251 Russia

*e-mail: pavlovav196@mail.ru

Abstract—Heat transfer during boiling in a large volume of subcooled pure water and water with the addition of Al_2O_3 microparticles is considered. The presented brief literature review indicates a clearly insufficient experimental base, without which it is impossible to talk about a direct dependence of the critical heat-flux density on the concentration of particles in a liquid. The methods used in the considered publications for studying heat transfer during boiling do not give a complete picture of the entire process and do not allow one to draw unambiguous conclusions. In the present work, the main research method was gradient thermal logging. The applied heterogeneous gradient heat-flux sensors made it possible to directly obtain local values of the heat-flux density (HTF) and proved to be a reliable tool in the study of phase transitions in a nonstationary formulation of the problem. The article considers three temperature differences, 384, 391, and 400°C, selected based on the resource of the model (time of uninterrupted operation of the model and primary converters) and in view of the stable film boiling mode characteristic of the critical values of the PTP. In the entire studied range of mass concentrations of Al_2O_3 microparticles from 1 to 4%, an intensification of heat transfer was observed during boiling of subcooled water at atmospheric pressure. The critical PTP for the considered temperature differences turned out to be 3.6–5.1 times higher than for pure water. For each temperature regime, the optimal concentrations of Al_2O_3 microparticles (particles) corresponding to the maximum PTP were revealed. An increase in the critical temperature in all modes and, as a consequence, in the local PHF is presumably due to a change in the thermophysical properties of the suspension and the perturbations introduced by these particles into the boiling process.

Keywords: gradient heatmetry, heterogeneous gradient heat-flux sensors, local heat-flux density, critical temperature, Al_2O_3 microparticles

Mixing of Different Temperature Flows of Liquid Sodium in the Pipeline Behind the Tee

I. V. Kolesnichenko^a, R. I. Khalilov^a, A. V. Shestakov^a, A. N. Krylov^b, V. V. Pakholkov^b,
A. M. Pavlinov^a, A. D. Mamykin^{a,*}, A. Yu. Vasiliev^a, S. A. Rogozhkin^b, and P. G. Frick^a

^a *Institute of Continuum Mechanics, Ural Branch, Russian Academy of Sciences, Perm, 614013 Russia*

^b *Afrikantov Experimental Design Bureau of Mechanical Engineering, Nizhny Novgorod, 603074 Russia*

**e-mail: mad@icmm.ru*

Abstract—Experimental studies into the process of mixing two different-temperature flows of sodium coolant in a T-shaped connection of cylindrical channels (tee) have been carried out. The measurements were carried out for two combinations of flow rates and temperatures of hot and cold sodium. The main result of the experiments is the characteristics of temperature fluctuations both in the sodium flow and on the outer surface of the tee pipes. Spectral analysis of signals from thermocouples located on the axis of the pipe in the mixing zone showed that the flow is turbulent in all cases. The average temperature of the pipe surface in regime 1 (the flow rate of cold sodium is approximately half the flow rate of hot sodium) in the observation zone increases monotonically with distance from the side (cold) branch pipe downstream as does the intensity of temperature fluctuations. In regime 2 (cold sodium consumption is comparable to hot sodium consumption), there is a small temperature dip in the middle of the observation region, which indicates the presence of a stationary return vortex in this region. In mode 2, the ripple level is lower than in mode 1 and is maintained over the entire measurement area. The amplitude of temperature fluctuations on the surface of the tee is significantly lower than in the flow, but the structure of the Fourier spectra is similar. With the help of a thermal imager, variations in the temperature field on the surface of the tee are visualized, which manifest themselves in the form of emerging and migrating with the flow areas with an increased amplitude of temperature pulsations. The process is not regular and does not indicate the presence of periodic temperature fluctuations on the wall. The spatio-temporal structure of the temperature pulsation field is analyzed by wavelet analysis methods, which make it possible to identify nonstationary quasi-periodic pulsations in a certain region of the channel and in a certain frequency range.

Investigation into the Emissivity of a Thin Tungsten Wire with Oxidized Surface in the Unsteady Heat Conduction Regime

M. G. Zeodinov^{a, b, *}, A. A. Pronkin^{a, b}, and D. A. Krynitskaya^b

^a *Joint Institute for High Temperatures, Russian Academy of Sciences, Moscow, 125412 Russia*

^b *National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia*

**e-mail: zeodinovmg@mpei.ru*

Abstract—Modern diagnostic tools offer a new approach to solving thermophysical problems, considerably saving measurement time: those measurements that previously required hours can now be made in just a few minutes. A procedure is proposed for determining the emissivity of a thin metal wire within several minutes in the regime of unsteady-state heat conduction. Many researchers, including G.M. Kondrat'ev, who proposed to determine the emissivity by the regular regime method, tried to implement this procedure in practice but faced technical problems inherent in experimental work, including the requirements for high vacuum and taking measurements using fast-response instruments. Technical difficulties forced researchers to limit the temperature range, increase the experiment time, or perform computer simulations of the heating-cooling process. This procedure can be implemented in practice due to the use of a fast-response measurement system based on an Arduino Uno microcontroller and an L-Card E14-140 analog-to-digital converter capable of recording signals at 40 ms intervals. Lithium-ion batteries were used to miniaturize the unit and reduce the interference level. The values of emissivity of a tungsten wire with an oxidized surface, determined by the selected and the calorimetric method in the temperature range of 400–870 K, are in good agreement. The temperature range is limited only by the voltage of the used battery.

Keywords: unsteady-state heat conduction, emissivity, tungsten wire with oxidized surface, cooling rate, radiative heat transfer

Study of Turbine Cascades at Negative Incidence Angles

B. I. Mamaev^a and G. V. Ermolaev^{a, *}

^a Lyulka Design Bureau, Branch of PAO ODK UMPO, Moscow, 129301 Russia

*e-mail: ermolaev_grigory@mail.ru

Abstract—Based on the analysis of experimental data, the influence of incidence angle on the blade loading and profile loss (hereinafter referred to as loss) in flat turbine cascades of axial turbines is refined. Wide ranges of geometric and operating parameters of sub- and transonic planar cascade are covered. It is shown that a negative incidence angle in terms of its effect on loss is a more complex phenomenon than a positive one. In the range of its moderate values, when a high velocity peak has not yet appeared on the blade pressure side near the leading edge, the improvement in loading on the suction side can overpower the deterioration in loading on the pressure side and incidence losses can become negative. Most cascades have a range of these negative incidence angle, in which the incidence angle loss is zero or first decreases, reaches a negative minimum, and then begins to increase. As the cascade convergence increases, the width of this range increases, and the losses decrease. As a rule, negative losses from the incidence angle are found in cascades in which, there is a velocity peak on the suction side near the edge under the design incidence. If a cascade with reduced convergence ratio and significant local diffusion ratio of the channel has a high velocity peak near the leading edge on the pressure side, then negative incidence angle leads to an increase in loss. To calculate the loss versus the incidence angle, it is advisable to divide the cascades into groups depending on the nature of the change in the loss versus the incidence angle and to establish the ranges of values of the main geometric parameters of the cascades common for each group.

Keywords: cascade, pressure side, leading edge, convergence ratio, negative incidence angle, flow exit velocity, blade loading, velocity peak, channel diffusion ratio, profile loss

Main Results of the Trial Test of a Closed Circuit with Natural Circulation of a Light-Water Coolant Under Supercritical Pressure

A. A. Sedov^{a, *}, P. S. Polyakov^a, S. B. Pustovalov^{a, **}, V. V. Parshin^a, and S. S. Simonov^a

^a National Research Centre Kurchatov Institute, Moscow, 123182 Russia

*e-mail: Sedov_AA@nrcki.ru

**e-mail: Pustovalov_SB@nrcki.ru

Abstract—Main results are presented of the trial tests of a closed loop with natural circulation (NC) of a light-water coolant under supercritical pressure (SCP), which is a part of the thermal engineering test facility at the site of the National Research Centre (NRC) Kurchatov Institute. Experimental data on a change in the distilled water heat transfer were obtained for an upward flow in a $\varnothing 6.0 \times 1.5$ mm stainless-steel tube with indirect electric heating at a specific heat load as high as 0.5 MW/m^2 and a mass velocity of up to $300 \text{ kg}/(\text{m}^2 \cdot \text{s})$ and also for a downward flow in a vertical tube bundle consisting of seven finned stainless-steel tubes with a size of $\varnothing 12.0 \times 2.5$ mm each in an upward natural convection air flow in the shell side. In addition, experimental data were obtained on the dynamics of heating of main equipment items in the loop circuit with natural convection of distilled water at supercritical pressure. These data were used to validate a code for calculation of the heater, cooler, and overall loop. The paper analyzes the features of the heating dynamics of the main equipment items in the closed loop with natural circulation of supercritical pressure water (SCW) as well as the specific of SCW heat transfer in four sections of the heater and cooler. In the experiments, the following main stages of SCW heating were experimentally revealed: heating of the pseudo-liquid, pseudo-phase change (pseudo-boiling), and heating of the pseudo-steam; in the cooler: cooling of the pseudo-steam, pseudo-phase change (pseudo-condensation), and cooling of the pseudo-liquid. The work was performed for substantiation of engineering and process solutions for a nonreactor loop of a water-moderated water-cooled power reactor (VVER-SCP) under an order of AO Concern Rosenergoatom.

Keywords: light water coolant, supercritical pressure, heat transfer, indirect electric heating of the coolant, coolant cooling, coolant natural circulation in a closed loop, VVER-SCP

Climate Change and Its Influence on the Energy Engineering Complex (Taking St. Petersburg as an Example)

D. A. Mil'kov^a, Yu. V. Yuferev^a, A. I. Tyutyunnikov^a, and A. S. Gorshkov^{a, *}

^a AO Gazprom Promgaz, St. Petersburg, 191124 Russia

*e-mail: A.Gorshkov@spb.promgaz.gazprom.ru

Abstract—Observations of the Earth climate for the last 100–150 years have revealed that the atmospheric air temperature in the ground level shows quite a rapid growth. Megalopolises and other settlements behave as large sources producing thermal pollution of the Earth air basin. Transport facilities, heated buildings, and heat and electric networks release a significant amount of energy, which accumulates in the air medium of cities and then dissipates into the surrounding space. The most rapid change in the air temperature has been noted for the last 50 years. The greatest increase of the outdoor air temperature, e.g., in St. Petersburg, is observed in the cold period of the year. It has been determined that the average air temperature in the cold period of the year (from October to April) has increased by 1.51°C, whereas the average air temperature increased by 0.72°C for the same interval of time but in the warm period of the year (from May to October), i.e., half as much as in the cold period. It has been found from studies of regulatory and reference documents that the standard climatic data specified in them lag significantly from the currently occurring climate changes. The article presents an analysis of the outdoor air temperatures in St. Petersburg for the period from 1992 to 2021 and an assessment of air temperatures in the coldest day and the coldest 5-day spell with reliabilities of 0.92 and 0.98 and also the absolute minimal air temperature for the considered 30-year interval of time. It is pointed out that the actual climatic indicators derived from statistical processing of daily data arrays are by 3–4°C higher than those specified in the relevant standards. As a result, when buildings are designed for the standard conditions specified by the existing regulations, the contractual loads turn out to be overestimated essentially in comparison with the actual ones, which is revealed in designing the configurations of settlement heat-supply systems. The consideration of actual climatic indicators opens up the possibility to decrease the contractual heat loads of consumers on a sound basis and, as a consequence, to achieve thermal energy saving without degrading the heat-supply quality.

Keywords: climate, standard climate indicators, outdoor air temperature, energy consumption, heat supply, heat loads