

Contents

Vol. 70, No. 8, 2023

Heat and Mass Transfer, Properties of Working Bodies and Materials

Prospects for the Use of Two-Dimensional Nanomaterials in Energy Technologies (Review)

A. S. Dmitriev and A. V. Klimenko

Spray Impingement Cooling of Metal Surfaces: a Review on Progressing Mechanisms (Review)

M. Jena, P. C. Mishra, and S. S. Sahoo

A Study of R113 Refrigerant Boiling Processes in a Horizontal Tube Bundle under High Heat Flux Conditions

O. O. Mil'man, V. B. Perov, G. G. Yan'kov, A. V. Kondrat'ev, A. V. Ptakhin, V. S. Krylov, A. P. Zheleznov, and A. A. Zhinov

Multi-Objective Optimization of Shell-and-Tube Heat Exchangers According to Different Expressions of the Second Law of Thermodynamics

M. B. R. Rodríguez, J. L. M. Rodríguez, M. Martins, O. P. de Lima, S. B. Santiago, M. R. Maduro, M. C. de Oliveira Junior, and N. J. de Oliveira Júnior

Renewable Energy Sources and Hydropower

Reforming of Hydrocarbon Fuel in Electrochemical Systems (Review)

A. A. Filimonova, A. A. Chichirov, N. D. Chichirova, and A. V. Pechenkin

Electrical Systems of Thermal and Nuclear Power Plants

The Effect of High-Temperature Superconducting Current Limiters on Short-Circuit Fault Clearing

D. A. Grigor'ev, O. Yu. Gusev, Yu. P. Gusev, and N. O. Posokhov

Metals and Strength Problems

Monitoring the Percentage of Service Life Usage for Unheated High-Temperature Elements of Boilers

E. A. Grin and D. N. Panfilov

Prospects for the Use of Two-Dimensional Nanomaterials in Energy Technologies (Review)

A. S. Dmitriev^{a, b, *} and A. V. Klimenko^{c, **}

^a National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

^b Graphene Institute, Moscow, 119019 Russia

^c National Research Technological University, Moscow Institute of Steel and Alloys (MISiS), Moscow, 119049 Russia

*e-mail: asdmitriev@mail.ru

**e-mail: klimenkoav@bk.ru

Abstract—The prospects for the use of new, two-dimensional nanomaterials (2D materials) for the intensification of heat and mass transfer processes in power equipment are considered. The main types of 2D materials are presented, and their physical and technological properties and unique characteristics are described. Separate technological methods for the manufacture of 2D materials and films, composites, and nanofluids for various energy applications have been studied. Special attention is paid to materials based on single-layer and multilayer graphene, characteristics of materials based on graphene components, and their physico-chemical and other parameters. The effects that are observed when using nanofluids as heat carriers and when applying coatings based on 2D materials on heat-transfer surfaces during various heat-transfer processes are described: single-phase convection, evaporation, boiling, condensation. It is shown that, in all cases, the heat-transfer efficiency increases significantly. Specific examples of the use of 2D materials in heat pipes and thermosiphons are given, and ways to improve the characteristics of these devices are described. Some mathematical and physical models of functioning of two-dimensional materials in power engineering are considered. Particular attention is paid to the peculiarities of the mechanisms of heat transfer, evaporation, boiling, and condensation in energy systems. However, it is indicated that there are certain difficulties in choosing 2D materials for use in the energy sector. It is concluded that, due to additional research and the active use of 2D materials, unprecedented opportunities are opening up for the development of promising energy, construction, electronic, and other technologies as well as the creation of next-generation materials with unique mechanical, optical, electromagnetic and thermal properties.

Keywords: heat and mass transfer, heat carriers, nanofluids, two-dimensional nanomaterials, graphene, film coatings heat pipe, drooping and film condensation, heat-transfer coefficient

Spray Impingement Cooling of Metal Surfaces: a Review on Progressing Mechanisms (Review)

M. Jena^a, P. C. Mishra^{a, *}, and S. S. Sahoo^b

*^a Thermal Research Laboratory (TRL), School of Mechanical Engineering, KIIT University,
Bhubaneswar, Odisha, 751024 India*

^b Department of Mechanical Engineering, Odisha University of Technology and Research (OUTR), Bhubaneswar, India

**e-mail: pcmishrafme@kiit.ac.in*

Abstract—In this paper, we present a review of the recent progresses in spray impingement heat transfer mechanisms and influences of various controlling parameters on spray impingement cooling performance. This paper focuses on the developments in spray cooling effectiveness achieved by modifying the flow processes and parameters. The open literature reveals that spray impingement cooling processes studies explore practical applications but not full understanding that can help to further improvement. There are many possibilities of improving the performance of spray cooling by alternating the fluid types, flow pattern and controlling parameters such as air/water pressure and to distance from nozzle to heated plate. Some of the earlier researchers have also tried pulsed spray impingement technique to enhance the heat transfer effectiveness during metal surface cooling. However, there remains a need for further examination and the present review discusses several such possibilities.

Keywords: Spray impingement cooling, pressure, mechanisms, pulsed spray method, economic factors, technical applications, working liquid, coolant

A Study of R113 Refrigerant Boiling Processes in a Horizontal Tube Bundle under High Heat Flux Conditions

O. O. Mil'man^{a, b, *}, V. B. Perov^a, G. G. Yan'kov^{b, d}, A. V. Kondrat'ev^{a, b, c}, A. V. Ptakhin^{a, b, c},
V. S. Krylov^{a, b}, A. P. Zheleznov^{a, c}, and A. A. Zhinov^c

^a NPVP Turbocon, Kaluga, 248010 Russia

^b Tsiolkovskii Kaluga State University, Kaluga, 248023 Russia

^c Kaluga Branch, Bauman Moscow State Technical University, Kaluga, 248000 Russia

^d National State Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

*e-mail: turbocon@kaluga.ru

Abstract—Energy-saving technologies are among the priority development lines of Russia's power industry. In recovering the rejected heat from geothermal sources, especially those located in cold climatic zones in which there is no access to service cooling water resources, it is profitable to use organic coolants, e.g., CFC refrigerants, as working fluid for dry cooling towers. The properties of such coolants have, as a rule, been studied to a sufficient detail in the region of low temperatures, because they are mainly used as working fluids for refrigeration systems at moderate heat fluxes. To obtain data on the boiling of organic coolants on a tube bundle for taking into account the influence of bundle lower tubes on the heat transfer in the upper tubes, a vapor generator mockup with a horizontal tube bundle was developed. High-pressure water served as the heating medium; and electric heaters were provided for additionally heating the CFC refrigerant to a level close to the saturation temperature. The tube bundle includes twelve tubes arranged in three rows along the height: the central row consists of four measurement tubes, and two lateral rows consist of auxiliary tubes. Eight thermocouples are installed at the top and bottom in the slots of the central row heat-transfer tubes for measuring the surface temperature. For the lower and upper rows in the bundle, boiling heat-transfer coefficients were obtained in a wide range of specific heat fluxes. It is shown that the boiling on the upper rows is significantly more (by 30–35%) intense than it is on the lower rows.

Keywords: heat transfer, CFC refrigerant, organic Rankine cycle, heat-transfer coefficient, low-grade heat, nucleate boiling, film regime, vapor generator, heat-transfer tubes, vaporization

Multi-Objective Optimization of Shell-and-Tube Heat Exchangers According to Different Expressions of the Second Law of Thermodynamics

M. B. R. Rodríguez^{a, *}, J. L. M. Rodríguez^a, M. Martins^a, O. P. de Lima^b, S. B. Santiago^c,
M. R. Maduro^b, M. C. de Oliveira Junior^c, and N. J. de Oliveira Júnior^b

^a Federal University of Bahia, Polytechnic Institute, Ondina, Salvador, 40170-110 Brazil

^b Amazonas State University, Manaus, Brazil

^c Amazonas Federal University, Belem, Ananindeua, Brazil

*e-mail: jorgemoyar@gmail.com

Abstract—Shell-and-tube type heat exchangers (STHE) are the most important part of non-combustion heat transfer equipment in industrial processes. The literature provides extensive information on various methods of optimizing the design of STHE, however, as a rule, it is carried out only with the aim of minimizing costs as an objective function. In this paper, it is proposed to use multi-purpose optimization of STHE using new thermodynamic and environmental expressions as objective functions. Its implementation is possible with the use of genetic algorithms of the second generation. The paper presents a procedure and a mathematical model for multi-purpose optimization, in which five objective functions are proposed to be used: the coefficient of thermal resistance, thermal efficiency, environmental function, total cost, including operating costs, and the total amount of dissipated entransy. The concept of entransy is proposed for the first time to create a new ecological function used as a criterion for optimizing STHE. The novelty of the proposed work lies in the fact that it optimizes simultaneously taking into account mechanical and vibration limitations, the design of the heat exchanger, as well as taking into account the parameters of thermohydraulic processes occurring in it. The approbation of the methodology was carried out on the basis of a specific case study, which had previously been repeatedly used by various authors to verify the results obtained. The multi-purpose optimization of the STHE made it possible to develop design options with minimal costs at a given thermal load and with geometric options that are adaptable to the space available for installation and the availability of auxiliary systems.

Keywords: entransy, optimization, shell-and-tube heat exchanger, the second law of thermodynamics, environmental efficiency, thermal resistance, cost, objective function, energy saving, irreversibility of the heat transfer process

Reforming of Hydrocarbon Fuel in Electrochemical Systems (Review)

A. A. Filimonova^{a, *}, A. A. Chichirov^a, N. D. Chichirova^a, and A. V. Pechenkin^a

^a Kazan State Power Engineering University, Kazan, 420066 Russia

*e-mail: aachichirova@mail.ru

Abstract—A review is presented of the designs and principles of operation of the systems for conversion of hydrocarbon fuel into synthesis gas (or syngas) to be used for energy generation in solid oxide fuel cells (SOFCs). Most SOFC systems employ methane or methane-rich (biogas, natural gas, industrial or petrochemical waste, etc.) as fuel due to their availability and ease of handling in contrast with hydrogen. The fuel-processing subsystem comprises approximately 50% of the overall electrochemical power facility. The generated heat, which is required for methane reforming, is recycled in fuel cells. Steam needed for the conversion of hydrocarbon fuel is generated in the anode compartment of the fuel cell or in an external steam generator recovering the heat of the exhaust gases of the fuel cell. The employed methods include steam reforming, partial oxidation of methane, carbon dioxide reforming of methane, and autothermal reforming. Steam reforming is the most extensively studied and widely used method. External reforming is employed for conversion of complex hydrocarbon fuels. For methane or natural gas, internal reforming is usually sufficient if the fuel recirculation ratio and steam to carbon and carbon to oxygen ratios are properly kept. Comparison of the existing methods for the production of syngas for SOFCs has revealed that steam reforming features the maximum steam consumption and the highest efficiency of the process. The partial oxidation of methane is an unsafe process due to the use of pure oxygen. Despite its low efficiency, the carbon dioxide conversion of methane offers the recovery of carbon dioxide and contributes additionally to decarbonization of the process. The autothermal reforming has merits of the steam reforming and the methane partial oxidation, but its implementation is a great challenge.

Keywords: solid oxide fuel cell, methane reforming, hydrocarbon fuel, hydrogen power engineering, partial oxidation of methane, carbon dioxide conversion of methane, electrochemical conversion

The Effect of High-Temperature Superconducting Current Limiters on Short-Circuit Fault Clearing

D. A. Grigor'ev^a, O. Yu. Gusev^a, Yu. P. Gusev^a, and N. O. Posokhov^{a, *}

^a National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

*e-mail: PosokhovNO@mpei.ru

Abstract—The article considers the influence of high-temperature superconducting (HTS) current limiters (CLs) on the requirements for peak withstand current, short-term withstand current, and breaking capacity of high-voltage circuit breakers in clearing single-phase short-circuit faults in 110-kV cable lines and estimates the influence of HTS CLs on transient recovery voltages (TRVs). Predicted and field oscillograms are compared with each other. In the case of using HTS CLs, it becomes possible to considerably reduce the requirements for high-voltage circuit breakers in terms of peak and short-term withstand current and breaking capacity, including the TRV peak and rate-of-change values. An alternative way for reducing the TRV peak and rate-of-change values, which makes it possible in many cases to do without expensive HTS CLs, is to use high-voltage circuit breakers fitted with shunt resistors. With such a solution, it becomes possible to not increase the automatic reclosing dead time caused by the need to cool the HTS CL after its actuation. The use of HTS CLs may be justified at high-capacity power plants and trunk substations with the level of short-circuit currents higher than 40 kA.

Keywords: high-temperature superconducting current limiters, cable lines, single-phase short-circuit faults, transient recovery voltages, high-voltage circuit breakers, peak withstand current, short-term withstand current, breaking capacity

Monitoring the Percentage of Service Life Usage for Unheated High-Temperature Elements of Boilers

E. A. Grin^{a, *} and D. N. Panfilov^a

^a *All-Russia Thermal Engineering Institute, Moscow, 115280 Russia*

**e-mail: EAGrin@vti.ru*

Abstract—The use of monitoring systems for assessment of the condition of operating equipment at thermal power plants (TPPs) is demonstrated to still be urgent. The applicable management procedures and monitoring processes provided for assessment of service life characteristics of high-temperature elements of equipment are analyzed. The shortcomings of these approaches are highlighted, and the advantages of monitoring and predictive diagnostics processes for a meaningful assessment of the technical condition and control of the service life characteristics of critical units and elements of power equipment operating under creep conditions are substantiated. The object of examination is a once-through supercritical boiler. Outlet headers of the high-pressure convective superheater, steam collection chambers, and crossover pipelines between these headers and chambers are adopted as critical elements of this boiler. The design and construction materials of these elements, the scheme of the steam flow in these sections of the flowpath, and the diagram of the monitoring of the operating conditions in them have been studied. The methodological concepts are outlined of the developed monitoring system, including provisions for the procedure for recording and systematization of the readings of standard temperature and pressure transducers, approaches to calculation of characteristics from these data, which are necessary to assess the residual service life of elements. The algorithm of the system is prescribed in the form of a step-by-step execution of calculation procedures during monitoring within the scope of the proposed physical model of the metal service life's expiry, which is based on regular relationships between the steam conditions and the operating time as well as on the properties of the metal. The stage of service life expiry is assessed by the principle of linear summation of accumulated damages. The specific is presented of the description in this algorithm of initially accumulated metal damages when a monitoring system is implemented in already operating equipment. Information is presented on a numerical check of the developed algorithm, including against actual data on the performance of the implemented monitoring system. Proposals are formulated on the procedure for assessing the condition of the metal within the scope of predictive diagnostics, carried out on the basis of the operating system.

Keywords: monitoring, boiler, high-temperature elements, creep, monitoring transducers, equivalent parameters, equivalent operating time, service life, algorithm, damageability, metal condition