

Contents

Vol. 71, No. 1, 2024

WE'RE 70!

3

General Energy Issues

Towards Climate Neutrality: Will Russian Forest Stand Against Energy?

V. V. Klimenko, A. V. Klimenko, and A. G. Tereshin

5

Transition to a Carbon Neutral Economy: Opportunities and Limitations, Current Challenges

S. P. Filippov

21

Heat Price Field Calculation Based on the Extreme Problem of Searching
the Optimal Load Flow in Heat-Supply Systems

V. A. Stennikov, O. V. Khamisov, A. V. Pen'kovskii, and A. A. Kravets

41

Steam-Turbine, Gas-Turbine, and Combined-Cycle Power Plants and Their Auxiliary Equipment

Low-Emission Combustion Chambers of GTU: Modern Trends, Diagnostics,
and Optimization (Review)

L. M. Chikishev and D. M. Markovich

50

Computational and Experimental Study of the Influence of the Intensity and Scale
of Flow Turbulence on Losses in a Nozzle Grid

A. V. Granovsky and B. I. Kurmanov

73

Steam Boilers, Power-Plant Fuels, Burner Units, and Boiler Auxiliary Equipment

Numerical-and-Experimental Substantiation of Deep Unloading
of an E-420-13.8-560GM Boiler

A. N. Tugov, V. M. Supranov, E. V. Somova, and V. A. Vereshchetin

87

Heat and Mass Transfer and Properties of Working Fluids and Materials

A Simple Method for Increasing the Boiling Critical Heat Flux

A. V. Dedov and M. D. Filippov

99

Towards Climate Neutrality: Will Russian Forest Stand Against Energy?

V. V. Klimenko^{a, b, c, *}, A. V. Klimenko^b, and A. G. Tereshin^{a, c}

^a National Research University Moscow Energy Institute, Moscow, 111250 Russia

^b National Research Technological University MISiS, Moscow, 119049 Russia

^c Energy Research Institute, Russian Academy of Sciences, Moscow, 117186 Russia

*e-mail: nilgpe@mpei.ru

Abstract—The prospects for reducing the carbon intensity of the Russian economy and the possibility of achieving climate neutrality of the country's national economy by 2060 are considered. Based on a historical-extrapolation approach to the study of the development of various socio-technical systems and by comparing the dynamics of carbon indicators of the economies of Russia and the leading countries of the world, it is shown that full compensation of anthropogenic greenhouse emissions gases when absorbed by the biosphere (primarily forests) is today rather only theoretically possible. The condition for this is the implementation of extremely ambitious large-scale reform programs in all sectors of the Russian economy, from energy to forestry. Thus, in an optimistic scenario, the rate of reduction in specific indicators of greenhouse gas emissions per capita should have the maximum values achieved in the world over the last 50 years: 1%/year. Forest management must include full compensation for increasing deforestation and a 50% reduction in forest losses from fires, which are currently the second (after energy) source of greenhouse gas emissions into the atmosphere. The most likely scenario is one in which the rate of reduction in specific greenhouse gas emissions per capita is 0.5%/year and a moderate increase in the absorption capacity of forests is ensured, mainly due to the implementation of forest climate projects and a reduction in fire emissions. If the latter scenario is implemented, net greenhouse gas emissions could amount to approximately 700 Mt CO₂(eq) by 2060, which will require the nation's carbon capture and storage industry on an unprecedented scale to achieve climate neutrality.

Keywords: economics, energy, forestry, greenhouse gas emissions and absorption, climate neutrality, historical extrapolation approach, scenarios, carbon capture and storage

Transition to a Carbon Neutral Economy: Opportunities and Limitations, Current Challenges

S. P. Filippov*

Energy Research Institute, Russian Academy of Sciences, Moscow, 117186 Russia

*e-mail: fil_sp@mail.ru

Abstract—Climate policy is gradually becoming dominant in the world and is beginning to decisively determine the long-term prospects for the development of the global economy and energy. The problem of curbing the rise in global temperature is global; therefore, reducing greenhouse gas emissions as a result of anthropogenic activities must be carried out in the most acceptable way for the global economy and energy sector. The optimal paths for countries around the world to transition to a carbon-neutral economy will vary significantly since they have different economic structures and endowments of energy resources. The article discusses the following technological directions of decarbonization of the economy: intensification of energy conservation, including production, transformation, transportation, and consumption of energy; changing the fuel structure in favor of low-carbon fuels by replacing coal with natural gas; replacing fossil fuels with carbon-neutral biomass; CO₂ capture in energy and industrial installations with its subsequent transportation and disposal; expanding the use of nuclear energy; and transition to the use of carbon-free renewable energy resources. For each of these areas, the potential for their contribution to achieving carbon neutrality in the economy and the existing restrictions on their implementation are identified. The research was carried out in relation to the economy and energy sector of Russia, which is one of the largest consumers and exporters of fossil organic fuels in the world. It is shown that the transition to a carbon-neutral economy must be complex and carried out through a combination of various technological solutions. The implementation of the “electric world” concept in the country, in which all basic energy needs will be met by using electricity produced on a carbon-free basis, until 2060 is hardly possible for technological and economic reasons, so the use of fossil organic fuels during this period will remain inevitable. At the same time, the issue of organizing the capture and disposal of CO₂ must be resolved.

Keywords: decarbonization, carbon neutrality, greenhouse gases, carbon dioxide, carbon dioxide capture and storage, energy, carbon neutral economy

Heat Price Field Calculation Based on the Extreme Problem of Searching the Optimal Load Flow in Heat-Supply Systems

V. A. Stennikov^a, O. V. Khamisov^a, A. V. Pen'kovskii^{a, *}, and A. A. Kravets^a

^aMelentyev Institute of Energy System, Siberian Branch, Russian Academy of Sciences, Irkutsk, 664033 Russia

**e-mail: penkoffsky@isem.irk.ru*

Abstract—The article proposes a method for calculating differentiated prices for heat at the nodes of a heat-supply system (HSS) based on the extreme economic formulation of the problem of searching for the optimal load flow in heat networks containing several heat sources. The problem boils down to finding the minimal total costs associated with heat generation and transportation, maintaining of material balances at heat network nodes (Kirchhoff's first law), and constraints imposed on the heat source capacities. The problem is solved on the basis of Lagrange's method of undetermined multipliers. An analysis of the initial optimization problem duality has shown that the dual variables (Lagrange's multipliers) in balance constraints are nothing but nodal prices for heat, and the optimal load flow in a heat network obtained in the calculation process makes it possible to form the price field for the system as a whole. It is also shown that the prices for heat from the heat sources to end consumers increase in the direction of the steady-state optimal load flow in the heat network. With such an approach to solving the problem, it is also possible to determine the optimal action zones and levels of loading the heat sources taking into account their cost characteristics and the specified heat network's physical, technical, and economic indicators. The nodal prices obtained from the calculations are in their economic essence marginal ones, i.e., prices based on calculating the limit low and limit high costs for generation and transportation of an additional unit of heat.

Keywords: heat-supply systems, optimization problem, optimal load flow, Lagrange's undetermined multipliers, nodal prices

Low-Emission Combustion Chambers of GTU: Modern Trends, Diagnostics, and Optimization (Review)

L. M. Chikishev^{a, b, *} and D. M. Markovich^a

^a Kutateladze Institute of Thermophysics, Siberian Branch, Russian Academy of Sciences, Novosibirsk, 630090 Russia

^b Novosibirsk State University, Novosibirsk, 630090 Russia

**e-mail: chlm@itp.nsc.ru*

Abstract—A brief overview of the designs of low-emission gas turbine-type combustion chambers is given using the example of aircraft propulsion systems. The most promising technology that helps reduce emissions of harmful substances is the combustion of a lean premixed fuel-air mixture, but its use is limited by nonstationary phenomena that have a significant impact on flame stabilization and lead to the occurrence of thermoacoustic resonance. Currently, this technology is implemented for high-power engines by only two companies: General Electric and Rolls-Royce. Work on creating a high-thrust engine in Russia is being carried out at AO UEC-Aviadvigatel within the framework of the PD-35 program. The problems of developing low-emission combustion chambers for gas pumping units are successfully solved at AO UEC-Aviadvigatel together with the Baranov Central Institute of Aviation Motor Development (GTU-16P). One of the key areas of energy development is also the development of high-power gas turbines of the classes GTE-65, GTE-170 (PAO Power Machines), GTD-110M (ODK Saturn), and here it is necessary to solve the same problems as for gas turbine engines. The most pressing problems are predicting the occurrence of thermoacoustic self-oscillations of gas in combustion chambers and controlling them using feedback both in nominal modes and in low-power modes. A review of technologies using low-emission combustion chambers is presented, and the current state of experimental studies of the flow structure and transfer processes in model combustion chambers is considered. Examples of advanced experimental stands that simulate flow and combustion in gas turbine-type combustion chambers are given and the necessary operating parameters and the technical solutions used are indicated that allow efficient measurements using modern optical diagnostic methods.

Keywords: combustion chamber, panoramic methods, combustion, gas turbine unit, low-emission combustion chambers, optical diagnostics of combustion processes, aircraft propulsion systems

Computational and Experimental Study of the Influence of the Intensity and Scale of Flow Turbulence on Losses in a Nozzle Grid

A. V. Granovsky^a, * and B. I. Kurmanov^a

^a *Lyulki Experimental Design Bureau, Moscow, 129301 Russia*

*e-mail: andrey.granovskiy@yandex.ru

Abstract—Despite the development of experimental and numerical methods for studying the effect of turbulence on the flow structure and gas-dynamic efficiency of turbine cascades, many questions arise when designing and improving the blade apparatus of high-temperature gas turbines. It is quite difficult to conduct reliable flow measurements or numerical studies for real-life turbomachinery operating conditions, where the range of changes in the intensity and scale of turbulence in the flow is difficult to predict. Therefore, to get closer to understanding how to more adequately take into account the influence of such parameters as the intensity and scale of turbulence when designing turbine arrays, a computational study of the gas turbine nozzle array was carried out, which was based on a number of experimental results obtained at the Central Institute of Aviation Engine Engineering. To assess the influence of the noted turbulence characteristics on the structure of the flow in the lattice, parametric studies were performed with different intensity values and scales of turbulence specified. In this work, based on experimental data obtained both with and without the use of various turbulators, the influence of the intensity and scale of turbulence on changes in the flow structure and profile losses in the nozzle array is analyzed in the range of values of the reduced (adiabatic) velocity at the exit from the array $\lambda_{2ad} = 0.55–0.95$. Computational studies were carried out using the 2D NS software package for the intensity of turbulence at the entrance to the nozzle array $Tu = 0.2–10\%$ and at different scales of turbulence.

Keywords: nozzle array, flow structure, profile losses, turbulator, superficial speed, turbulence intensity, turbulence scale, gas turbine

Numerical-and-Experimental Substantiation of Deep Unloading of an E-420-13.8-560GM Boiler

A. N. Tugov^{a, *}, V. M. Supranov^b, E. V. Somova^a, and V. A. Vereshchetin^a

^a All-Russia Thermal Engineering Institute, Moscow, 115280 Russia

^b National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

*e-mail: ANTugov@vti.ru

Abstract—One of the main characteristics of the maneuverability of power equipment is whether the load may be reduced to the minimum allowable level. The ability of power equipment to operate in a variable regime (with unloading during night time) enables it to participate in the control of frequency and power in the power system. It is important to note that low-load operation of the equipment should not make its performance poorer. In particular, for drum boilers, the required steam conditions and reliable circulation of the working fluid in the evaporation waterwalls should be maintained in the entire operating load range. The numerical-and-experimental studies have substantiated the possibility to reduce the minimum allowable steam load of a typical E-420-13.8-560GM boiler from 210 to 150 t/h. According to the results of thermal design calculations by the Boiler-Designer code, the required steam superheat temperature (560°C) cannot be attained at lower loads. Field tests of an operating boiler have revealed that difficulties with fuel flow control and failures of the furnace's combustion process arise at loads below 150 t/h. Calculations and experimental measurements performed using flow measuring tubes installed in the furnace waterwalls have demonstrated that the fluid circulation of a fluid in the evaporation water walls remains even on a load decrease to 110 t/h. It is pointed out that more than 100 E-420-13.8-560GM boilers, whose design was modified during long-term operation (for more than 40 years), are operating now. Therefore, the minimum steam load should be finalized only after additional studies for each boiler of this type.

Keywords: boiler, steam capacity, minimum load, circulation, thermal engineering tests, superheater, fuel flow, heat absorption nonuniformity factor

A Simple Method for Increasing the Boiling Critical Heat Flux

A. V. Dedov^a and M. D. Filippov^{a,*}

^a National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

*e-mail: filippovmd@mpei.ru

Abstract—The article considers a study of the possibility to increase the boiling critical heat flux q_{cr} through the use of surfaces consisting of areas with different heat conductivity. The results of experiments on studying pool boiling heat transfer for saturated dielectric fluid methoxynonafluorobutane (Novec 7100) on bimetallic surfaces are presented. The studies were carried out for bimetallic samples and also for samples made of copper and grade 08Kh18N10T stainless steel in the pressure range 0.1–0.4 MPa. A description of the experimental setup and the procedures used is given. The boiling curves for each sample in the entire presented range of fluid pressures with a step of 0.1 MPa are obtained, and the tables of critical heat-flux values are given. The effect that the liquid pressure has on the relative increase of q_{cr} for bimetallic samples is shown. The values of q_{cr} obtained on all samples are compared with one another, and the increase of q_{cr} on bimetallic surfaces by up to 20% is shown. The previously performed studies are briefly reviewed, and the experimental data obtained by other researchers on boiling heat transfer on surfaces with modulated heat conductivity and for boiling of Novec 7100 fluid are presented, including that on samples with a modified heat-transfer surface. The obtained results are compared with rather few data of other researchers. The temperature field in a bimetallic sample is numerically simulated, and the temperature distribution over the heat-transfer surface is presented. The growth of q_{cr} is due to nonisothermal properties of the heat-transfer surface, which causes the boiling to become regularized.

Keywords: boiling, bimetallic sample, critical heat flux, boiling curve, saturated fluid, modified heat-transfer surface, modulated heat conductivity