

Contents

Vol. 73, No. 1, 2026

Environment Protection

Neutralization of Effluent Water and Dangerous Waste in Supercritical Water-Oxygen Fluid: Review

O. N. Fedyaeva and P. A. Strizhak

Heat and Mass Transfer and Properties of Working Fluids and Materials

Numerical and Experimental Study of Thermal-Hydraulic Processes in the Convergent-Divergent Channels of Plate Heat Exchangers with Etched Channels

V. O. Kindra, I. A. Maksimov, D. V. Patorkin, O. V. Zlyvko, and I. I. Komarov

Studying the Vortex Heat Transfer Enhancement during Turbulent Air Flow over a Plate with a Limited Package of Inclined Oval-Trench Dimples Using Numerical Modeling and Gradient Thermometry Methods

*S. A. Isaev, S. Z. Sapozhnikov, V. V. Seroshtanov, V. Yu. Mityakov,
D. V. Nikushchenko, S. A. Knyazev, and A. A. Klyus*

Thermal-hydraulic Characteristics of Mini Cooling Towers Equipped with Film Regular Contacting Devices

E. A. Lapteva, R. N. Khamidullin, and A. G. Laptev

Steam Boilers, Power Plant Fuel, Burners and Boiler Auxiliary Equipment

Energy and Environmental Combustion Efficiency of Steam-Atomized Liquid Fuel with Controlled Blast Dilution

E. Yu. Shadrin, I. S. Sadkin, and E. P. Kop'ev

Water Treatment and Water Chemistry

Monitoring and Control of Water Chemistry in the Power Unit Turbine Generator Water Cooling System

A. B. Larin, B. M. Larin, M. P. Savinov, and E. G. Ukhalova

Neutralization of Effluent Water and Dangerous Waste in Supercritical Water-Oxygen Fluid: Review

O. N. Fedyaeva^{a, *} and P. A. Strizhak^b

^a *Kutateladze Institute of Thermophysics, Siberian Branch, Russian Academy of Sciences, Novosibirsk, 630090 Russia*

^b *National Research Tomsk Polytechnic University, Tomsk, 634050 Russia*

**e-mail: fedyaeva@itp.nsc.ru*

Abstract—The article analyzes the main achievements in the field of neutralizing effluent water and dangerous halogen containing waste by oxidizing them in water in supercritical state (at temperature $t > 374^{\circ}\text{C}$ and pressure $p > 22.1$ MPa). Criteria determining the oxidation efficiency are revealed. Problems connected with practical implementation of the discussed approach are formulated, first of all, corrosion of structural materials and deposition of salts. Technical solutions that help improve waste neutralization efficiency, reduce corrosion, and prevent pipelines becoming blocked with solid particles and mineral components are described. The environmental and economic aspects of industrial application of supercritical water oxidation are considered. The conditions for achieving better energy and environmental efficiency of oxidizing waste jointly with conventional fuel kinds are determined. Prospects of applying supercritical water oxidation at thermal power plants for ultrasupercritical steam conditions are noted.

Keywords: effluent water, dangerous waste, supercritical water oxidation, corrosion, structural materials, salt deposition

Numerical and Experimental Study of Thermal-Hydraulic Processes in the Convergent-Divergent Channels of Plate Heat Exchangers with Etched Channels

V. O. Kindra^{a, *}, I. A. Maksimov^a, D. V. Patorkin^a, O. V. Zlyvko^a, and I. I. Komarov^a

^a National Research University Moscow Power Engineering Institute, Moscow, 111250 Russia

*e-mail: kindra.vladimir@yandex.ru

Abstract—The cost and efficiency of power installations depend in many respects by the design characteristics of heat transfer equipment. These characteristics are especially important for gas turbine units with regenerators operating on low boiling coolants with low temperature differences and high pressure differences. For such high-efficient energy systems with regeneration, the use of plate heat exchangers containing microchannels obtained by chemical etching of their surface holds promise. For improving their thermal-hydraulic efficiency, versions of extended heating surfaces with convergent-divergent channels are proposed in the article. A set of calculated and experimental studies of the newly developed channels for plate heat exchangers was carried out. Convective heat transfer was numerically simulated, the results of which made it possible to determine the influence of key geometrical parameters, namely, the relative segment length L/H and expansion amplitude A/H on the thermal-hydraulic characteristics in a wide range of Reynolds number values ($2500 \leq Re \leq 15\,000$). It is shown that with a periodically narrowed and widened channel cross section, flow acceleration and deceleration zones are produced; directed action on the boundary layers takes place, and turbulent mixing is enhanced. This helps eliminate stagnant zones and obtain more uniform distribution of heat removal over the surface. Based on mathematical modeling, correlation dependences for the Nusselt number and hydraulic coefficient as functions of the Reynolds number have been obtained, which are suitable for engineering assessments of the efficiency of heat exchangers with similar geometrical parameters of the channels. To verify the numerical study results, an experimental setup was developed, and tests of channel models with recording the heat transfer and pressure losses were carried out, which have confirmed the correctness of the theoretical approach and repeatability of the revealed regularities. The obtained results can serve for confirming the rational choice of geometrical parameters and practical applicability of modified plate heat exchangers with chemically etched channels as part of compact regenerators of advanced power facilities.

Keywords: enhancement, heat transfer, hydraulic resistance, overflows, thermal-hydraulic efficiency, Nusselt number, friction coefficient

Studying the Vortex Heat Transfer Enhancement during Turbulent Air Flow over a Plate with a Limited Package of Inclined Oval-Trench Dimples Using Numerical Modeling and Gradient Thermometry Methods

S. A. Isaev^{a, b}, S. Z. Sapozhnikov^c, V. V. Seroshtanov^{c, *}, V. Yu. Mityakov^c,
D. V. Nikushchenko^b, S. A. Knyazev^c, and A. A. Klyus^a

^a Saint-Petersburg State University of Civil Aviation named in honor of Chief Marshal of Aviation A.A. Novikov,
St. Petersburg, 196210 Russia

^b Saint-Petersburg State Marine Technical University, St. Petersburg, 190121 Russia

^c Peter the Great St. Petersburg Polytechnic University, St. Petersburg, 195251 Russia

*e-mail: vladvik1992@gmail.com

Abstract—The article presents a numerical and experimental study of separated flow and heat transfer in limited packages of four inclined oval-trench dimples (OTDs) located on a heated isothermal section of an adiabatic plate in uniform air flow with the Reynolds number $Re = 3 \times 10^4$. The depth of dimples is equal to 0.25 of their width, and the slope angle is 45° . The isothermal section temperature is maintained with superheated steam. The results of numerical calculations carried out by solving the Reynolds averaged Navier – Stokes equations in the VP2/3 software package, which are closed by the differential equations of the shear stress transfer model (RANS with the SST turbulence model) and the equation of energy, were validated by comparing them with the experimental data obtained by means of gradient thermometry techniques on the thermophysical setup at the St. Petersburg Polytechnic University. Multiblock computation technologies with the use of intersecting meshes of different scales were applied. It has been found that, with shifting the dimples away from the plate leading edge, relative heat transfer and back flows are enhanced. With a shift from the first to the fourth dimple, the relative Nusselt number increases in the inlet parts at the bottom by a factor of two (from 1.2 to 2.4) and by a factor of 1.7 (from 1.5 to 2.6) in the windward edge area. The stabilization of stagnation pressure on the windward slopes at a level of 0.26 with the minimal pressure equal to -0.15 in the vortex generation zones entails enhancement of back flows. The static pressure differences cause enhancement of back flows in packaged dimples. The study results have revealed fundamental differences in the heat transfer distribution between the first and subsequent dimples, as well as in their end parts.

Keywords: heat transfer enhancement, package of inclined oval-trench dimples, turbulence, gradient thermometry

Thermal-Hydraulic Characteristics of Mini Cooling Towers Equipped with Film Regular Contacting Devices

E. A. Lapteva^{a, *}, R. N. Khamidullin^b, and A. G. Laptev^a

^a Kazan State Power Engineering University, Kazan, 420066 Russia

^b Kazan National Research Technological University, Kazan, 420015 Russia

*e-mail: Grivka100@mail.ru

Abstract—The article presents the results of experimental studies of the hydraulic and mass transfer characteristics of 1 m high roll polymeric mesh packing having a specific surface area of $240 \text{ m}^2/\text{m}^3$, equivalent diameter of 0.015 m, and free specific volume of 0.95, with a film countercurrent flow regime in the column with a spray density of $5.0\text{--}25.0 \text{ m}^3/(\text{m}^2 \text{ h})$ and air velocity of $0.5\text{--}2.5 \text{ m/s}$. The air pressure difference, volumetric mass transfer coefficient, and air humidification efficiency with water are determined. Generalized empirical formulas for calculating these characteristics are derived. The roll polymeric mesh packing is compared with regular packings made of corrugated metal tape and corrugated vertical metal plates with a rough surface in terms of specific pressure difference and mass transfer efficiency. The possibility of using these packings in mechanical-draft mini cooling towers is considered. An algorithm for calculating the mini cooling tower efficiency and cooled water temperature after its having been in contact with air is presented. Graphic dependences of the hydraulic and heat-and-mass transfer characteristics on the operating parameters are given. Special attention is paid to an analysis of liquid distribution over the packing surface and liquid film formation, which is a key factor for intense mass transfer. A reasonable ratio between the air velocity and spray density under different operation conditions is determined. The study results can be used in design and modernization of water cooling systems, including those at industrial enterprises, in which it is necessary to maintain highly efficient heat transfer and use the most compact equipment.

Keywords: cooling tower, heat and mass transfer, water cooling, process efficiency, contacting packings, pressure difference, hydraulic resistance

Energy and Environmental Combustion Efficiency of Steam-Atomized Liquid Fuel with Controlled Blast Dilution

E. Yu. Shadrin^{a, *}, I. S. Sadkin^a, and E. P. Kop'ev^a

^a *Kutateladze Institute of Thermophysics, Siberian Branch, Russian Academy of Sciences, Novosibirsk, 630090 Russia*

**e-mail: evgen_zavita@mail.ru*

Abstract—The aim of the work is to study the effect of diluting gases (nitrogen, carbon dioxide, and steam) and oxygen on the combustion of liquid fuel atomized with superheated steam. Main attention is paid to optimizing the combustion process environmental and power performance characteristics. Experiments were carried out using a laboratory burner with fuel atomized by means of steam into a preliminary gas generation chamber, in which atomized fuel is mixed with blast of various compositions. Operating conditions with addition of diluting agents at room temperature and with heating them to 250°C, as well as cases with the use of oxygen-enriched blasting, were studied. The study results have shown that the temperature of supplied gases plays the key role in the combustion process: in admitting cold dilution agents, the flame temperature decreased by 150–200°C, and the chemical reactions slowed down, whereas when heated gases were admitted, the high flame temperature remained unchanged. With increasing the oxygen fraction, a growth of temperature was observed. It has been determined that the ingress of cold diluting agents in the fuel entailed a more efficient reduction of NO_x и CO emissions in comparison with the operating conditions with admission of a heated mixture. At the same time, the admission of heated gases resulted in lower emissions under the operating conditions with oxygen enrichment. Injection of steam resulted in a lower production of NO_x, but it entailed higher CO emissions and caused the combustion to become unstable. By using the method proposed in the article, it is possible to reduce the NO_x emissions (up to 50%), which is commensurable with this indicator in the case of conventional recirculation of flue gases, but with a lower fraction of them (5–10% against 20–30%). This makes the technology involving steam-assisted atomization and controlled dilution of fuel a promising option for use in the power industry and metallurgy, sectors in which high energy efficiency and environmental safety are of importance.

Keywords: liquid fuel combustion, superheated steam, diluting gases, NO_x, recirculation, environmental indicators

Monitoring and Control of Water Chemistry in the Power Unit Turbine Generator Water Cooling System

A. B. Larin^{a,*}, B. M. Larin^a, M. P. Savinov^a, and E. G. Ukhalova^a

^a *Ivanovo State Power Engineering University, Ivanovo, 153003 Russia*

^{*}*e-mail: yaandy_81@mail.ru*

Abstract—Electrical conductivity, pH, and oxygen concentration continuously measured in circulation water are the key monitored parameters of the water chemistry (WC) in a power unit turbine generator water cooling system. With a shift for the use of water cooling in the turbine generator systems at thermal power plants (TPP) and for designing of such systems for turbine generators of the T3V-1200-2AU3 series at NPPs, problems were encountered in ensuring the standardized circulation water quality indicators and in WC control. The article presents a method for determining by calculation the standardized values of electrical conductivity and pH in metering NaOH in a circulating cooling system (CCS) depending on these indicators in makeup water (water medium with low buffering capacity). The turbine generator water cooling systems serve for intense heat removal from the stator (and rotor) windings and are widely used in the power units at TPPs and NPPs. The quality of cooling (circulation) water is standardized with respect to several indicators, of which the electrical conductivity and pH are the main ones. In view of quite stringent standards on electrical conductivity, especially for the turbine generator rotor cooling system (below $1.43 \mu\text{S}/\text{cm}$), there is nothing to do but use deeply demineralized weakly acidic water ($\text{pH} < 7.0$), and it is not permitted to use ammonia. For the acidity to be neutralized with NaOH solution, very accurate controlled metering is required: with an insufficient quantity of NaOH, the pH will be below 6.5 (the lower limit), and with an excessive quantity of NaOH, the pH value will exceed 9.0, which is the upper permissible limit for CCS. A mathematical model of ionic equilibria in the CCS circulation water is constructed and solved. With NaOH metered within the range of permissible values, the electrical conductivity and pH value adjustment boundaries are determined depending on the source and makeup water quality. An author's certificate for a software product has been received. Given the existing makeup water quality and unchanged CCS process circuit arrangement, the performed study makes it possible to recommend installing an automated system for metering NaOH solution into circulation water based on the prescribed electrical conductivity value.

Keywords: power unit turbine generator, water chemistry, caustic soda solution metering, cooling water chemistry monitoring and control